

Occupancy Sensor - Residential In-Wall Push Button PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-DPBIF-WHMX



NOM

PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. The sensor switch can turn a load ON and hold it as long as the sensor detects occupancy. After no motion is detected for the set time delay, the load turns OFF automatically. The sensor switch has one relay (equal to single pole switch), it also includes Ambient Light Level Sensor

FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection
- ▶ Adjustable PIR sensitivity
- ▶ Adjustable time delay 15 sec to 30 min
- ▶ Adjustable ambient light sensor override for occupancy switch models
- ▶ Coverage: 150°, 980 ft2 with non-obstructed views
- ▶ IOS-DPBIF and IOS-DPBV models are Incandescent/Fluorescent/CFL/LED compatible and require a neutral connection
- ▶ 'No neutral' models offered for retrofit applications
- ▶ Fits standard decorator wall plate (included)
- ▶ Occupancy (Automatic ON/ Manual or Automatic OFF)
- ▶ For use with Magnetic Ballasts

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-DPBIF-WHMX
Description	Residential In-Wall Push Button PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275125254
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA
Control Specifications	
Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	30 lux
Adjustable Light Level Max	Daylight
PIR Coverage Area (sq ft)	980
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
PIR Coverage Pattern (degrees)	150
Maximum Mounting Height (ft)	4 ft
Mount Type	In-Wall

Dimensions	
Product Height (in)	2.75
Product Height (mm)	70
Product Width (in)	1.438
Product Width (mm)	37
Product Depth (in)	1.625
Product Depth (mm)	41
Material Specifications	
Color	White
Includes Wall Plate	Yes
Load Ratings	
Tungsten Range(s)	800 W
Resistive Load Ratings Ranges	12 A
Motor Load Ratings Ranges	1/4 HP, 120/125 VAC
Ballast Ranges	800 VA
Electrical Specifications	
Input Voltage Range(s)	120/125 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Hz	60
Packaging	
Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	5 x 2.25 x 3 in
Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C
Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	X