

Cartridge Filters - 36 Sq Ft Diatomaceous Earth (DE) Filter (short)

Item APF036PRO



PRODUCT DESCRIPTION

Remove dirt and debris down to 5 microns our high performance D.E. series filters. These Eco friendly solutions are an upgrade to standard sand filters and require minimal maintenance.

FEATURES

- ▶ Universally compatible NPT setup provides hassle-free installation and maintenance.
- ▶ Single D.E. (Diatomaceous Earth) element.
- ▶ 2 NPT female fittings.
- ▶ Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
- ▶ Easy-to-read pressure gauge allows for quick performance assessment.
- ▶ Works well with low speeds.
- ▶ Large drain plug.
- ▶ Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
- ▶ Manual air relief valve pre-installed from the factory.
- ▶ 6 ft. Cord with a standard plug.

APPLICATIONS

- ▶ Above Ground and In-Ground Pool and Spa

TECHNICAL DATA

General	
Model Number	APF036PRO
Description	36 Sq Ft Diatomaceous Earth (DE) Filter (short)
UPC Code	816965015818
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	1-Year limited
Filter Area (Sq Ft)	36
Min Service Clearance	39"
Filter Element Height	26 5/8"
Cartridges Required	1
Diatomaceous Earth Required	3.5 lbs
Turnover Capacity 6 hour (gallons)	25,920
Turnover Capacity 8 hour (gallons)	34,560
Turnover Capacity 10 hour (gallons)	43,200
Max Working PSI	50
Replacement Filter Element	62559-AQP1
Turnover Capacity 6 hour Max Flow (gallons)	32,400
Turnover Capacity 8 hour Max Flow (gallons)	43,200
Turnover Capacity 10 hour Max Flow (gallons)	54,000
Maximum Flow Rate (GPM)	90

Material Specifications

Color	Black
-------	-------

Packaging	
Shipping Weight (lbs)	29
Unit Carton Dimensions (H x W x L) in	25.5 x 16.5 x 16.5 in
Unit Package Quantity	1
Operating Specifications	
Recommended Water Flow GPM	72
Standards and Certifications	
California Proposition 65	DEHP
RoHS Certification	X