

# Plug-In Timer - Outdoor Mechanical Plug-In Timer with Built-In Enclosure.

Item P1101



## **PRODUCT DESCRIPTION**

These plug-in timers are grounded and utilize a flip-open enclosure rated for outdoor use. These heavy-duty timers are great for providing timer function to pumps, landscaping or holiday lighting. 24-hour timers come with 2 On and 2 Off settings.

## **FEATURES**

- ▶ 2 ON/2 OFF settings per day with removable trippers, more ON/OFF events with addition of extra trippers.
- ► Minimum 30-min ON/OFF time.
- ► Built into outdoor rated enclosure with clear or black flip cover.
- ► Grounded standard NEMA 5-15 plug and receptacle.
- Plugs directly into wall outlet.

## **APPLICATIONS**

- ► Outdoor Lighting Control
- ► Landscape Water Control
- ► Pool Pump
- Outdoor Water Fountains

## **TECHNICAL DATA**

Color

Load Ratings

| General                           |   |
|-----------------------------------|---|
|                                   | Dates   |
| Model Number                      | P1101   |
| Description                       | Outdoor Mechanical Plug-In Timer with Built-In Enclosure. |
| UPC Code                          | 078275061118  |
| Brand                             | Intermatic  |
| Country of Origin (Intermatic)    | MEXICO  |
| Warranty Period                   | 1-Year limited  |
| TARIC HS Code                     | 9107.00.00  |
|                                   |   |
| Control Specifications            |   |
| Minimum 0N/0FF Times              | 30 min  |
| ON/OFF Operations                 | 2   |
| Mechanism Type                    | Analog/Mechanical   |
| Application Compatibilities       | Incandescent; Tungsten                                    |
|                                   |   |
| Mechanical Specifications         |   |
| Plug Configurations               | 5-15  |
| Mount Type                        | Plug-ln   |
|                                   |   |
| Dimensions                        |   |
| Product Dimensions (H x W x D) in | 5.375 x 5.125 x 2.5 in                                    |
| Cord Size                         | 22"   |
|                                   |   |
| Material Specifications           |   |

Black and Clear



Resistive Heater 15 A, 120 VAC

Incandescent Load Ratings 1800 W, 120 VAC, 60 Hz

Motor Load Ratings Ranges 1 HP, 15 FLA, 90 LRA @ 120 VAC

**Electrical Specifications** 

Input Voltage Range(s) 120 VAC, 60 Hz
Hz 60

Amperage 20 A

Packaging

Shipping Weight (lbs) 1.297

Unit Carton Dimensions (H x W x L) in 7.75 x 3.81 x 5.75 in

**Environmental Specifications** 

Usage Environments Outdoor

Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities Green Energy

California Proposition 65 DEHP

RoHS Certification



## **ACCESSORIES**



107TN221

Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222

Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS