

Photocontrol - Locking Type Thermal Photocontrol, 120 V, Mexico Sales Only

Item LC4521MX



NOM

PRODUCT DESCRIPTION

These photocontrols install on light fixtures with ANSI C136.10 NEMA receptacles commonly found on street light fixtures. Locking type design facilitates fast installation and replacement of photocontrol.

FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Integral high impact thermoplastic housing
- ▶ Locking type plug for quick installation and changeover
- ▶ Delay feature prevents unwanted OFF switching
- ▶ Complies with ANSI C136.10 standard
- ▶ Tested to 3,650 ON/OFF cycles

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	LC4521MX
Description	Locking Type Thermal Photocontrol, 120 V, Mexico Sales Only
UPC Code	078275127821
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	2-Year limited
Control Specifications	
Sensor Time Delay	30 sec to 60 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1.5 fc
Activation Off	4.5 fc
Photocontrol Type	Thermal
Application Compatibilities	LED; Incandescent; HID
Photocontrol Style	Locking type
Photocontrol Sensor Location	Side
Dimensions	
Product Height (in)	1.969
Product Height (mm)	50
Product Diameter (in)	2.91
Product Diameter (mm)	74
Material Specifications	
Color	Transparent

Housing Material	Polycarbonate
------------------	---------------

Load Ratings

Magnetic Ballast Range(s)	8.3 A, 1000 VA
Tungsten Range(s)	15 A, 1800 W

Electrical Specifications

Input Voltage Range(s)	120 VAC, 50/60 Hz
Hz	50/60

Packaging

Shipping Weight (lbs)	0.449
Unit Carton Dimensions (H x W x D) in	2 x 3 x 3 in

Operating Specifications

Expected Lifetime (Years)	20
Expected Lifetime (Operations)	3650

Environmental Specifications

Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
Usage Environments	Outdoor

Standards and Certifications

Other Certifications and Compatibilities	NOM; Ansi C136.10
California Proposition 65	None
RoHS Certification	X

ACCESSORIES



K121
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 9" lead



K121-30
Locking Type Receptacle, 3-Pin, C136.10
Compliant, 30" lead



K122
Locking Type Receptacle, 3-Pin, C136.10
Compliant, with Pole Mounting Bracket



K171H
Locking Type Receptacle, 7-Pin, C136.41
Compliant, 12" lead



KPT1170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Dusk-to-Dawn, 10' cable



KPT0170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 10' cable



SK4500K
Shorting Plug for Locking Type Receptacles



KPT0170-015
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 15' cable



SK4500KMX
Shorting Plug for Locking Type Receptacles