

Photocontrol - Locking Type Receptacle, 3-Pin, C136.10 Compliant, with Pole Mounting Bracket, Mexico Sales Only

Item K122MX



PRODUCT DESCRIPTION

The K122 NEMA receptacles provide the connector interface for locking type photocontrols. They can be installed in the light fixture itself, or attached externally with the use of a mounting bracket (included).

FEATURES

- ▶ NEMA receptacle with 3-prong sockets
- ▶ Compliant to ANSI C136.10 specifications

TECHNICAL DATA

| General                               |                                                                                                  |
|---------------------------------------|--------------------------------------------------------------------------------------------------|
| Model Number                          | K122MX                                                                                           |
| Description                           | Locking Type Receptacle, 3-Pin, C136.10 Compliant, with Pole Mounting Bracket, Mexico Sales Only |
| UPC Code                              | 078275501201                                                                                     |
| Brand                                 | Intermatic                                                                                       |
| Country of Origin (Intermatic)        | CHINA                                                                                            |
| Warranty Period                       | 1-Year limited                                                                                   |
| Dimensions                            |                                                                                                  |
| Product Height (in)                   | 2.13                                                                                             |
| Product Height (mm)                   | 54.1                                                                                             |
| Product Diameter (in)                 | 2.56                                                                                             |
| Product Diameter (mm)                 | 65.02                                                                                            |
| Material Specifications               |                                                                                                  |
| Color                                 | Black                                                                                            |
| Base Material                         | Phenolic                                                                                         |
| Bracket Material                      | Aluminum                                                                                         |
| Back Cover Material                   | Phenolic                                                                                         |
| Power Contacts Material               | Brass/Phosphor Bronze                                                                            |
| Gasket                                | (Integrated) Thermal Elastomer                                                                   |
| Wire Leads                            | #14 AWG, 105°C, AWM3321                                                                          |
| Electrical Specifications             |                                                                                                  |
| Power Contacts Rating                 | 480 V max, 15 A max                                                                              |
| Packaging                             |                                                                                                  |
| Shipping Weight (lbs)                 | 0.35                                                                                             |
| Unit Carton Dimensions (H x W x D) in | 6.381 x 3.251 x 3.251 in                                                                         |

Environmental Specifications

|                         |                                      |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 176 °F / (-40 °C to 80 °C) |
|-------------------------|--------------------------------------|

Standards and Certifications

|                                          |      |
|------------------------------------------|------|
| Other Certifications and Compatibilities | NOM  |
| California Proposition 65                | None |
| RoHS Certification                       | X    |