

Item Bundle - Freeze Protection 4/8 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure

Item PF1222TB1



PRODUCT DESCRIPTION

Protects pool/spa equipment against freeze damage.

FEATURES

- ▶ GFCI and switch mounting capabilities
- ▶ Turns pump and heater ON when outdoor temperature drops below user-adjustable setpoint on thermostat
- ▶ Heavy-duty Type 3R metal indoor/outdoor enclosure

APPLICATIONS

- ▶ Protection
- ▶ Pump Control

TECHNICAL DATA

| General                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Number                      | PF1222TB1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Description                       | Freeze Protection 4/8 Breaker Base Panel with 2 Timers and Thermostat for 240V Cleaner Applications, Heater Protection, Type 3R Metal Enclosure                                                                                                                                                                                                                                                                                                                                              |
| UPC Code                          | 078275141131                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Brand                             | Intermatic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Country of Origin (Intermatic)    | MEXICO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Warranty Period                   | 1-Year limited                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Control Specifications            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Heater Protection Switch          | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Mechanical Specifications         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Number of Breaker Knockouts       | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Enclosure Type                    | 3R Beige metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Dimensions                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Product Dimensions (H x W x D) in | 16.875 x 10.875 x 4.75 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Material Specifications           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Color                             | Beige                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Load Ratings                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Load Center Ratings               | 100 A, 120-208 VAC, 60 Hz;85 A, 120-208 VAC, 60 Hz;80 A;80 A, 208 VAC, Single Phase;60 A;60 A, 208 VAC, Single Phase;125 A;125 A, 208 VAC, Single Phase;80 A, 240 VAC, 60 Hz, Single Phase;80 A, 120-240 VAC, 50 Hz;80 A, 120 VAC, 60 Hz;60 A, 240 VAC, 60 Hz, Single Phase;60 A, 120-240 VAC, 50 Hz;60 A, 120-208 VAC, 60 Hz;125 A, 240 VAC, 60 Hz, Single Phase;125 A, 120-240 VAC, 50 Hz;125 A, 120-208 VAC, 60 Hz;100 A, 240 VAC, 60 Hz, Single Phase;85 A, 240 VAC, 60 Hz, Single Phase |
| Load Center Rating Display        | 60 A Max, 120/240 VAC, Single Phase, 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Motor Load Ratings Ranges         | 3 HP @ 240 VAC, 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

| Electrical Specifications             |      |
|---------------------------------------|------|
| Number of Circuits                    | 2    |
| Switch Type                           | DPST |
| Maximum Power Consumption (W)         | 3 W  |
| Number of Receptacle/Switch Knockouts | 1    |
| Hz                                    | 60   |

| Packaging                             |                         |
|---------------------------------------|-------------------------|
| Shipping Weight (lbs)                 | 18.712                  |
| Unit Carton Dimensions (H x W x L) in | 6.25 x 12.25 x 18.25 in |

| Operating Specifications      |     |
|-------------------------------|-----|
| Thermostat Range Minimum (°C) | 0.5 |
| Thermostat Range Minimum (°F) | 33  |
| Thermostat Range Maximum (°C) | 6   |
| Thermostat Range Maximum (°F) | 42  |

| Standards and Certifications             |              |
|------------------------------------------|--------------|
| CSA Certification                        | cCSAus       |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | Lead         |
| RoHS Certification                       | X            |

ACCESSORIES



156T1978A  
Extra/replacement trippers 1 ON and 1 OFF



21T166A  
Spacer-Standoff, 3" long - 2 pack



21T156A  
Spacer-Standoff, 3" long - 4 pack

130LV1091  
Terminal Block 2-Pole