

Electronic Timer Control - 24-Hour/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor/Outdoor Plastic Enclosure

Item ET2105CP



PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application. They come in standard 24-hour versions.

FEATURES

- ▶ 100-hour supercapacitor eliminates the need for batteries.
- ▶ Up to 96 set points or events.
- ▶ Up to 50 holiday blocks with schedule capabilities.
- ▶ Automatic input voltage selection from 120 to 277 VAC, 60 Hz.
- ▶ Additional mode of operation turns the ON/OFF buttons into 2-hour overrides.
- ▶ Configurable outputs allow the control of various voltages and applications.
- ▶ Relays incorporate zero-crossing technology to extend the life of the control.
- ▶ Non-volatile EEPROM memory protects programming indefinitely.
- ▶ LED compatible.
- ▶ USB port makes transferring and saving of schedules easy.

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

TECHNICAL DATA

General	
Model Number	ET2105CP
Description	24-Hour/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor/Outdoor Plastic Enclosure
UPC Code	078275147973
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Maximum ON/OFF Operations	96
Setpoint Program Count	96
ON/OFF Operations	96
Operation Features	Holiday
Operation Mode	24 hour
Daylight Savings Adjustment	Automatic
Backup Restoration Time	30 Minutes
Backup Type	Supercapacitor
Backup Protection Time	100 Hour

Application Compatibilities	LED
-----------------------------	-----

Mechanical Specifications

Enclosure Type	Outdoor type 3R plastic
----------------	-------------------------

Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Material Specifications

Color	Gray
-------	------

Communication Method

Has WiFi	No
----------	----

Load Ratings

Electronic Ballast LED	10 A
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120-240 VAC
Inductive Load Ratings NO Ranges	30 A, 120-240 VAC
Electronic Ballast Load Ratings NO Ranges	10 A, 120/277 VAC
Tungsten (NO) Range(s)	5 A, 120-277 VAC
Motor Load Ratings NO Ranges	1 HP, 120 VAC; 2 HP, 240 VAC

Electrical Specifications

Voltage Selection Type	Auto Voltage
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	3 W
Electronic Series	ET2000 Series
Hz	60

Packaging

Shipping Weight (lbs)	2.25
Unit Carton Dimensions (H x W x L) in	10 x 3.937 x 6.5 in

Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
------------------	-------



Other Certifications and Compatibilities	LED; Title 20; Green Energy +
California Proposition 65	Lead
RoHS Certification	X