

Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-CMP-ULCMX



NOM

PRODUCT DESCRIPTION

Este sensor de infrarrojo pasivo (PIR) detecta la diferencia del calor emitido por un cuerpo humano en movimiento y el espacio de fondo. El sensor enciende la luz controlada y la luz se mantiene encendida siempre que el sensor detecte alguna presencia. El sensor apaga la luz controlada cuando no detecta movimiento después de un tiempo de retardo ajustable.

FEATURES

- PIR technology sensing for presence detection
- Coverage: 1200 ft2 when mounted on 8 to 11 ft ceiling
- Zero-crossing technology for long life and performance
- Adjustable ambient light sensor override
- Requires neutral connection
- Incandescent/Fluorescent/CFL/LED compatible

APPLICATIONS

- Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-CMP-ULCMX
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275149274
Brand	Intermatic
Warranty Period	1-Year limited
Country of Origin (Intermatic)	CHINA
Control Specifications	
Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	3 sec
Adjustable Time Delay Max	30 min
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Mechanical Specifications	
PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Mount Type	Ceiling
Material Specifications	
Color	White
Load Ratings	
Electronic Ballast Load Ratings Ranges	100-200 W

Electrical Specifications

Input Voltage Range(s)	120/277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Hz	50/60

Packaging

Shipping Weight (lbs)	0.72
Shipping Weight (kg)	0.327
Unit Carton Dimensions (H x W x L) in	2.25 x 5.82 x 5.82 in

Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	X