

Electronic Timer Control - Electronic Pump Motor Controller with Seasonal Adjustment, 4-Circuit, Mechanism Only

Item P1403ME









PRODUCT DESCRIPTION

Control single- and two-speed pumps and auxiliary equipment with this 3-circuit programmable device. The seasonal adjustment feature can be programmed to automatically adjust filter pump ON/OFF schedules according to the season.

FEATURES

- ► Saves up to 40% in monthly utility bills compared to standard timers
- ► Meets most rebate incentives
- ► Enables separate daily schedules
- ► Easy-to-follow on-screen setup for programming
- ► Autovoltage adjust
- ► Efficient low-speed operation for all seasons
- ► User programmable high and low-speed events
- ► 100+ hour supercapacitor memory retention
- ► Available with Type 3R indoor/outdoor lockable metal enclosure

APPLICATIONS

- ► Motor Control
- ► Pump Control

TECHNICAL DATA

General	
Model Number	P1403ME
Description	Electronic Pump Motor Controller with Seasonal Adjustment, 4-Circuit, Mechanism Only
UPC Code	078275139947
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited

Control Specifications		
Minimum ON/OFF Times	1 min	
Maximum ON/OFF Times	23 hours, 59 minutes	
Maximum 0N/0FF Operations	3	
ON/OFF Operations	3	
Daylight Savings Adjustment	Automatic	
Backup Type	Supercapacitor	

Material Specifications	
Color	Black

Communication Method	
Has WiFi	No

Load Ratings	
Tungsten Range(s)	5 A @ 120-277 VAC, 50/60 Hz
Inductive	30 A @ 24 VAC, 60 Hz; 30 A @ 24 VAC, 50 Hz; 120-277 VAC



 Resistive Load Ratings Ranges
 30 A @ 24 VAC, 120-277 VAC, 50/60 Hz; 20 A @ 28 VDC

 Inductive Load Ratings Ranges
 30 A @ 24 VAC, 120-277 VAC, 50/60 Hz

Motor Load Ratings Ranges 16 FLA, 96 LRA @ 120 VAC, 50/60 Hz; 17 FLA, 80 LRA @ 240 VAC, 50/60 Hz

 Electrical Specifications

 Input Voltage Range(s)
 120-277 VAC, 50/60 Hz

 Number of Circuits
 3

 Switch Type
 4-SPST

 Maximum Power Consumption (W)
 7 W

 Hz
 50/60

 Packaging

 Shipping Weight (lbs)
 1.657

 Unit Carton Dimensions (H x W x L) in
 4.25 x 7.25 x 11.5 in

Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities Title 20; Green Energy

California Proposition 65 DEHP

RoHS Certification X