

Item Bundle - 60 A Load Center with T104M Mechanism, 4-Breaker Spaces

Item T21004R



PRODUCT DESCRIPTION

This system can be used as a load center only, or add a heavy-duty mechanical time switch or wiring devices for a complete system.

FEATURES

- ▶ Four breaker spaces
- ▶ Accepts PF1000M, P1403ME, P1353ME, P4043ME, P4243ME,T100M or RC2000M Series mechanisms
- ▶ Accepts many interchangeable type breakers
- ▶ Load center dead front has two knockouts for switches or GFCIs and one on the side
- ▶ Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

APPLICATIONS

- ▶ Distribution/Control Panel
- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

General	
Model Number	T21004R
Description	60 A Load Center with T104M Mechanism, 4-Breaker Spaces
UPC Code	078275083462
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Breaker Knockouts	4
Enclosure Type	3R Beige metal
Dimensions	
Product Dimensions (H x W x D) in	16.875 x 8.875 x 4.75 in
Knockout Dimensions Bottom	(5) combination 1/2" - 3/4" and (3) combination 3/4" - 1"
Knockout Dimensions Back	(1) combination 1/2" - 3/4" and (1) 3/4" - 1"
Knockout Dimensions Left	(1) combination 1/2" - 3/4"
Knockout Dimensions Right	(1) 1 3/4" x 2 3/4"
Material Specifications	
Color	Beige
Load Ratings	
Tungsten Range(s)	40 A, 120-240 VAC, 60 Hz
Inductive	40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz
Load Center Ratings	60 A, 120-208 VAC, 60 Hz;60 A, 240 VAC, 60 Hz, Single Phase
Resistive Load Ratings Ranges	40 A, 120-240 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-240 VAC, 60 Hz

Pilot Duty Load Ratings Ranges	1000 VA, 120-240 VAC, 60 Hz
Load Center Rating Display	60 A, 120/240 VAC or 120/208 VAC, Single Phase
Mechanism Supply Voltage	240 VAC, 60 Hz
Mechanisms	T104M
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz

Electrical Specifications	
Number of Circuits	1
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Number of Receptacle/Switch Knockouts	2
Hz	60

Packaging	
Shipping Weight (lbs)	12.225
Unit Carton Dimensions (H x W x L) in	6.001 x 10 x 17.751 in

Environmental Specifications	
Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)

Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	X

ACCESSORIES



156T1978A
Extra/replacement trippers 1 ON and 1 OFF




21T166A
Spacer-Standoff, 3" long - 2 pack



21T156A
Spacer-Standoff, 3" long - 4 pack



156T2978A
Package Accessory Trippers



22T338GR
Mounting Bracket for Intermatic Standardized
Timer Mechanisms

22T713
Bracket Painted

8--00008A
Latch-Enclosure

124--00139A
4-Pole Buss Bar Assembly

156PA13715A
1" Nonmetallic Hub Kit