

Mechanical Time Switch - 24-Hour Mechanical Time Switch with Skip-a-Day, 208-277 VAC, 60Hz, SPDT, Outdoor Metal Enclosure, 15 Minute Interval

Item T1976R



PRODUCT DESCRIPTION

This series of mechanical time switches offers more flexible scheduling capabilities by offering 15-minute intervals. These units also come with trippers that slide in or out easily for fast and accurate settings. All units can control up to 20 A of electrical load and have a single pole, double throw switch.

FEATURES

- ▶ Provides up to 96 operations (48 ON/48 OFF) every 24 hours
- ▶ Models with skipper wheel allow for operations to be omitted on selected days of the week
- ▶ 15-minute intervals
- ▶ Captive trippers slide in and out of dial for fast, accurate setting

APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	T1976R
Description	24-Hour Mechanical Time Switch with Skip-a-Day, 208-277 VAC, 60Hz, SPDT, Outdoor Metal Enclosure, 15 Minute Interval
UPC Code	078275118010
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	15 min
Maximum ON/OFF Operations	48
Skipper Wheel	24 Hour
Operation Mode	24 hour
Has Manual Override	Yes

Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Number of Trippers Included	96

Dimensions	
Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#12 AWG

Material Specifications	
Color	Gray

Load Ratings	
Resistive Load Ratings Ranges	20 A, 125-480 VAC, 60 Hz
Motor Load Ratings Ranges	1/2 HP, 125 VAC, 60 Hz; 1 HP, 250 VAC, 60 Hz

Electrical Specifications	
Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W
Hz	60
Amperage	20 A

Packaging	
Shipping Weight (lbs)	3.642
Unit Carton Dimensions (H x W x L) in	4.25 x 7.25 x 11.75 in

Environmental Specifications	
Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)

Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
CSA File Number	C22.2-177; LR3730
California Proposition 65	Lead
RoHS Certification	X

ACCESSORIES



156T1950A
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series

156T1950AD12
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



22T338GR
Mounting Bracket for Intermatic Standardized Timer Mechanisms



133T698A
Replacement Snap Switch for T1970 Series



WG730-14D
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14DMX
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



156T1957A
Skipper Screws (3 per package)



156T2978A
Package Accessory Trippers



WG736-14D
480 V, 60 Hz Motor for T1900, T8800, R8800 Series