

Mechanical Time Switch

- 24-Hour Heavy-Duty Metal Dial Mechanical Time Switch, 125 VAC, 60Hz, SPDT, Outdoor Metal Enclosure, 15 Minute Interval

Item T1905HDR



PRODUCT DESCRIPTION

These heavy-duty time switches are designed to handle the toughest environments and have fully encapsulated motors to prevent dust or debris from entering the motor. The ON/OFF trippers are permanently attached to the metal dial to avoid the accidental loss of a tripper. These time switches offer 15-minute intervals, providing up to 96 operations each day.

FEATURES

- ▶ Heavy-duty metal dial and metal enclosure withstands the most punishing environmental conditions
- ▶ Models with skipper wheel allow for operations to be omitted on selected days of the week
- ▶ Easy-to-set trippers rotate in/out for fast, accurate setting
- ▶ Up to 96 operations (48 ON/48 OFF) every 24 hours
- ▶ 15-minute intervals between events
- ▶ Fully encapsulated motor with protected gears

APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	T1905HDR
Description	24-Hour Heavy-Duty Metal Dial Mechanical Time Switch, 125 VAC, 60Hz, SPDT, Outdoor Metal Enclosure, 15 Minute Interval
UPC Code	078275142985
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	15 min
Maximum ON/OFF Operations	48
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Number of Trippers Included	96
Dimensions	
Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#12 AWG
Material Specifications	

Color

Gray

Load Ratings

Resistive Load Ratings Ranges	20 A, 125-480 VAC, 60 Hz
Motor Load Ratings Ranges	1/2 HP, 125 VAC, 60 Hz; 1 HP, 250 VAC, 60 Hz

Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	125 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W
Hz	60

Packaging

Shipping Weight (lbs)	3.892
Unit Carton Dimensions (H x W x L) in	8.5 x 3.25 x 5.5 in











Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	X

ACCESSORIES

			
<p>156T1950A</p> <p>Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series</p>	<p>156T1950AD12</p> <p>12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series</p>	<p>22T338GR</p> <p>Mounting Bracket for Intermatic Standardized Timer Mechanisms</p>	<p>124T907A</p> <p>Insulator Assembly (S001)</p>
			
<p>WG730-14D</p> <p>125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series</p>	<p>WG730-14DMX</p> <p>125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series</p>	<p>WG733-14D</p> <p>208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series</p>	<p>WG733-14DMX</p> <p>208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series</p>
			
<p>156T1957A</p> <p>Skipper Screws (3 per package)</p>	<p>156T2978A</p> <p>Package Accessory Trippers</p>	<p>WG736-14D</p> <p>480 V, 60 Hz Motor for T1900, T8800, R8800 Series</p>	