

## Lighting Controllers - 2-Channel 0-10 V Lighting Controller

Item ALC2-R



### PRODUCT DESCRIPTION

The ALC2-R lighting controller is a two-channel 0-10 V dimming controller designed to work with ARISTA® Lighting Control System by Intermatic. These units can work with either 0-10 V or 1-10 V lighting fixtures, including LED's. Once installed, the ALC2-R unit(s) can be configured to work off of either scheduling, sensing, or a combination of both, providing maximum energy efficiency as well as occupant comfort. These units can be configured for either wireless or wired communications, and utilize Bluetooth Mesh technologies for wireless communications. Pricing is available upon request.

### FEATURES

- ▶ Wired or wireless communications.
- ▶ Provides 24 VDC for wired devices.
- ▶ Utilizes a secure bluetooth mesh for connectivity.
- ▶ Built-in real time clock for keeping timing accuracy.
- ▶ Allows for 1 wired analog Input.
- ▶ Allows for 2 wired digital inputs.
- ▶ Works with 0-10 V or 1-10 V luminaires.
- ▶ 365-Day scheduling including holidays.
- ▶ Programmable blink warning alert.
- ▶ Programmable light levels.

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Dimming

### TECHNICAL DATA

General	
Model Number	ALC2-R
Description	2-Channel 0-10 V Lighting Controller
UPC Code	078275150782
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA
Control Specifications	
Operation Features	Holiday; Astronomic; Daylight Saving Time; Countdown
Operation Mode	365 day; Countdown
Data Transfer Options	Bluetooth
Daylight Savings Adjustment	Automatic
Backup Type	Supercapacitor
Backup Protection Time	100 Hours
On/Off Operations per Channel	256
Application Compatibilities	LED
Function type	Dimming; Remote Controllable; Scheduled Dimming; Scheduled ON/OFF
Mechanical Specifications	
Plenum Rated	Yes
Mount Type	Surface

Dimensions		
Product Height (in)		8.25
Product Height (mm)		209.55
Product Width (in)		8.25
Product Width (mm)		209.55
Product Depth (in)		3
Product Depth (mm)		76.2
Material Specifications		
Color		White
Material		Plastic
Communication Method		
Radio signal		Bluetooth
Low Voltage		Analog; Digital
Load Ratings		
Magnetic Ballast Range(s)		16 A, 120-277, VAC
Tungsten Range(s)		12.5 A, 277 VAC
Electronic Ballast Load Ratings Ranges		16 A, 120-277 VAC
Tungsten Load Ratings		12.5 A
Resistive Load Ratings Ranges		20 A, 120-277 VAC
Electronic Ballast LED		16 A
Electrical Specifications		
Voltage Selection Type		Auto-Voltage 120-277
Input Voltage Range(s)		120-277 VAC, 60 Hz
Switch Type		2xSPST
Neutral Connection Required		Yes
Wiring Options Line Voltage		Pigtails
Wiring Options Low Voltage		Pigtails; Terminals
Hz		60
Power Connection		
External inputs		Analog; Digital
Display and Format		
Status Indicator		LED
Packaging		
Shipping Weight (lbs)		5.6
Shipping Weight (kg)		2.54
Product Weight (kg)		2.041
Product Weight (lbs)		4.5

Operating Specifications	
Programming Targets	Smartphone
Tampering protection	Yes

Environmental Specifications	
Temperature (operation)	32°F..131°F
Temperature (operation)	0°C..55°C
Usage Environments	Indoor

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Ashrae 90.1 2016; IECC 2018; Green Energy +
California Proposition 65	None
RoHS Certification	Y