

Electronic Refrigeration Control

- Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 110-240 VAC, Screw Terminals, RS485, Propane Suitable

Item BIT25-B1S3W-BI



PRODUCT DESCRIPTION

Split Controllers are designed to excel in more demanding applications and provide additional control options for more complex equipment. These controllers can be mounted to a wiring chase or with the refrigeration equipment, eliminating the need for long runs of control wiring. \*Controller, cable and display must each be ordered separately

FEATURES

- ▶ Multi-voltage
- ▶ Remote mounting
- ▶ Remote connectivity
- ▶ Manage multiple alarms
- ▶ Heating or cooling

APPLICATIONS

- ▶ Ice Refrigeration Machine
- ▶ Reach-In Refrigeration Cooler

TECHNICAL DATA

General	
Model Number	BIT25-B1S3W-BI
Description	Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 110-240 VAC, Screw Terminals, RS485, Propane Suitable
UPC Code	078275150935
Brand	LAE
Country of Origin (Intermatic)	ITALY
Warranty Period	5-Year limited

Control Specifications	
Minimum Cycle Time	1 min
Mechanism Type	Electrical
Defrost LED Indicator	Red
Has Real-time Clock Face	No
Application Compatibilities	Commercial Refrigeration; Walk-in Cooler; Walk-in Freezer

Mechanical Specifications	
Mounting Options	DIN
Enclosure Type	IP55 Front
Enclosure Mounting Type	Screw

Dimensions	
Product Dimensions (H x W x D) in	1.57 x 3.27 x 2.76 in
Panel Opening Height (in)	1.14
Panel Opening Height (mm)	29
Panel Opening Width (in)	2.80
Panel Opening Width (mm)	71

Cut-Out Width (In)	2.80
Cut-Out Width (mm)	71
Cut-Out Height (in)	1.14
Cut-Out Height (mm)	29
Wire Size Max	#10 AWG

Material Specifications

Color	Black
-------	-------

Load Ratings

Resistive Load Ratings Ranges Compressor	12 (12) A @ 240 VAC
Resistive Load Ratings Ranges AUX1	16 A @ 240 VAC
Resistive Load Ratings Ranges AUX2	4 A @ 240 VAC

Electrical Specifications

Voltage Selection Type	Auto-Voltage
Wiring Option	Screw terminal block
Input Voltage Range(s)	230 VAC ±10%, 50/60 Hz
Number of Circuits Controlled	3
Electrical Life	100,000 operations at full load
Relay Type Compressor	SPST
Relay Type Fan	SPST
Relay Type AUX1	SPST
Relay Type AUX2	SPST
Hz	50/60

Display and Format

Clock Display Types	LED
---------------------	-----

Packaging

Shipping Weight (lbs)	0.46
Product Weight (kg)	0.29
Unit Carton Dimensions (H x W x L) in	2.8 x 3.6 x 4.8 in
Product Weight (lbs)	0.64

Environmental Specifications

Storage Temperature Min (°F)	14
Storage Temperature Max (°F)	122
Storage Temperature Min (°C)	-10
Storage Temperature Max (°C)	50
Operating Humidity	0-80% RH, Non-condensing
Temperature (operation)	14 °F to 122 °F / (-10 °C to 50 °C)

Standards and Certifications

RoHS Directive	2011/65/EU.
UL Certification	UL60730-1

Other Certifications and Compatibilities	Title 24 LAE; NSF; Green Energy
UL File Number	#SA32385
California Proposition 65	None
RoHS Certification	Y

ACCESSORIES



SN4B50P1  
Temperature Probe, NTC 10k probe, 5.0 m, Gray



SN4B30P1  
Temperature Probe, NTC 10k probe, 3.0 m, Gray



SN4B20P1  
Temperature Probe, NTC 10k probe, 2.0 m, Gray



SN4B20P2-B  
Temperature Probe, NTC 10k probe, 2.0 m, Blue



SN4B20P3-Y  
Temperature Probe, NTC 10k probe, 2.0 m, Yellow



SN4B30P2-B  
Temperature Probe, NTC 10k probe, 3.0 m, Blue



SN4B30P3-Y  
Temperature Probe, NTC 10k probe, 3.0 m, Yellow



SN4B50P2-B  
Temperature Probe, NTC 10k probe, 5.0 m, Blue



SN4B50P3-Y  
Temperature Probe, NTC 10k probe, 5.0 m, Yellow



LCD-5S-1I  
Display, BIT25