

Graesslin Mechanical Time Switch - 7-Day 120V Electromechanical Panel Mount Timer Module with Battery Backup and Manual Override, 2 Hour Intervals, 21A, SPDT

Item FM1QWUZH-120U



PRODUCT DESCRIPTION

The FM1 series timer modules are designed to be integrated inside of a machine control panel, circuit board, or other equipment. They are a simple and low cost alternative for applications that do not require more than 21 A or 2 HP, 240 VAC. The FM1 is designed for 24-hour or 7-day control or overriding a functional typical state of a heating, ventilation, refrigeration, lighting, security, or pump system. The FM1 series is ideal for 12, 24 VAC/VDC, 120 or 208/240VAC single-phase general applications.

FEATURES

- ▶ 21 A SPDT Switch
- ▶ Captive trippers with 15-minute intervals on 24-hour models and 2-hour intervals on 7-day models
- ▶ 72-hour carry-over battery backup on Q models
- ▶ Noise immune – ideal for robust applications
- ▶ Synchronous drive or quartz drive Q models with self-recharging battery backup
- ▶ True clock face, easy-to-set
- ▶ Available with or without override
- ▶ Compact size
- ▶ Clear plastic cover (DC-FME-A), sold separately
- ▶ Standalone or with indoor/outdoor enclosure, sold separately

APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	FM1QWUZH-120U
Description	7-Day 120V Electromechanical Panel Mount Timer Module with Battery Backup and Manual Override, 2 Hour Intervals, 21A, SPDT
UPC Code	078275152663
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Maximum Cycle Time	7 days
Timing Interval	2 hrs
Clock Drive Type	Quartz
Backup Type	72-hour Carry-over; Battery; Self-recharging
Battery Type	NiMh
Backup Protection Time	72 Hours
Battery Service Type	Rechargeable
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes

Has Real-time Clock Face	Yes
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Mounting Options	Panel
------------------	-------

Dimensions

Product Dimensions (H x W x D) in	2.359 x 2.359 x 1.25 in
-----------------------------------	-------------------------

Material Specifications

Color	Black
-------	-------

Load Ratings

Motor Load Ratings Ranges	1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz
---------------------------	--

Electrical Specifications

Maximum Power Consumption (VA)	1
Wiring Option	1/4" Quick connect terminals
Switch Type	SPDT

Display and Format

Shortest switching time	ON/OFF 2 hours
-------------------------	----------------

Packaging

Shipping Weight (lbs)	0.24
Unit Carton Dimensions (H x W x L) in	2.25 x 3.25 x 3.25 in

Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
Temperature (operation)	-4 °F to 131 °F / (-20 °C to 55 °C)
Operating Temperature with Battery Backup	-4° F to 131° F (-20° C to 55° C)

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	cRUus; Green Energy
UL File Number	E10694
CSA File Number	LR3730
California Proposition 65	None
RoHS Certification	N/A