

RC-LRSK1-WH - Long-Range Wireless Switch with Remote Control Fob Bundle



PRODUCT DESCRIPTION

The Long-Range Wireless Switch with Remote Control Fob is designed for use with Intermatic pool and spa panels, Intermatic weatherproof covers, and similar weather-rated NEMA 3R enclosures. Featuring 915 MHz spread spectrum wireless technology, the switch communicates with the included remote control fob at distances up to 400 feet through metal panels, with no external antenna required. The internal components of the Long-Range Wireless Switch have been treated with a special coating to resist oxidation in outdoor environments and supports an operating temperature range of -30° C to 70° C (-22° F to 158° F), while the fob supports an operating temperature range of 0° C to 50° C (32° F to 122° F).

FEATURES

- Convenient all-in-one package contains everything you need to control pool lights and other outdoor lighting up to 400 feet away.
- Ruggedized switch for long life and enhanced reliability in NEMA 3R outdoor enclosures.
- 915 MHz wireless technology provides extended range and remarkable performance, even through metal panels.
- Switch has operating temperature range of -30° C to 70° C (-22° F to 158° F), while fob has an operating temperature range of 0° C to 50° C (32° F to 122° F).
- Includes both the Long-Range Switch (RC-LRS1-WH) and the Remote Control Fob (RC-LRSR-WH) in a single convenient kit.
- Box Contents: (1) long-range wireless switch, (1) faceplate (2) faceplate mounting screws, (2) electrical box screws, (4) wire connectors, (1) remote control fob, (2) AAA batteries, installed (1) wall bracket, (2) wall bracket screws, (1) visor clip, (2) quick installation guides.

APPLICATIONS

- Landscape Lighting
- Pool Lighting Control

TECHNICAL DATA

General

Model Number	RC-LRSK1-WH
Description	Long-Range Wireless Switch with Remote Control Fob Bundle
UPC Code	078275158931
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Operation Mode	On/Off
Battery Type	AAA
Battery Service Type	Replaceable
Battery life	Up to 10 years
Data Transfer Options	Long-range 915 MHz; Remote Operation
Wireless Signal Range Ft	400
Chemical Composition of the Battery Cell	Alkaline
Number of Batteries Included	2

Material Specifications

Color	White
-------	-------

Load Ratings

General Purpose	5 A
-----------------	-----

Electronic Ballast LED	600 W
Tungsten Load Ratings	600 W

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz; 3 VDC
Hz	60

Environmental Specifications

Temperature (operation)	-22 - 158 °F / -30 - 70 °C
-------------------------	----------------------------

Packaging

Shipping Weight (lbs)	0.6
Unit Carton Dimensions (H x W x D) in	5 x 2.938 x 2.969 in

Standards and Certifications

Other Certifications and Compatibilities	cETLus; FCC; IC: 29501-3604; Green Energy
California Proposition 65	None
RoHS Certification	N
CA Prop 65 Message	This product is in compliance with Prop65
PDF Standards And Certifications	Green Energy; FCC; cETLus
Epi Certifications	cETLus; FCC; Green Energy

URL's

Software DownLoad URL	View FAQs
-----------------------	---