

## In-Wall Timer - 7-Day Heavy-Duty Programmable Timer, 120-277 VAC, 20A, Light Almond

Item EI600LAC



### PRODUCT DESCRIPTION

Highly versatile Heavy-Duty Timers are ideal for any application that requires a simple or complex ON/OFF schedule, regardless of load. No neutral connection is required. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- Versatile 7-day programmable schedules with up to 40 ON/OFF events
- Astronomic clock feature determines dawn and dusk times
- Automatic Daylight Saving Time (DST) adjustment
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Isolated switch allows timer to be used with any load type, including AC and DC loads
- Replaceable CR2 lithium battery provides up to three years of operation
- No neutral wire connection enables easy retrofitting and quicker installation
- Decorator switch plate not included

### APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation
- Outdoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	EI600LAC
Description	7-Day Heavy-Duty Programmable Timer, 120-277 VAC, 20A, Light Almond
UPC Code	078275101425
Brand	Intermatic
Country of Origin (Intermatic)	VIETNAM
Warranty Period	5-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	40
Operation Mode	24 hour
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	3 Years
Battery Type	CR2 Lithium
Battery Service Type	Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Lithium
Number of Batteries Included	1
Battery Weight (grams)	11.08
Number of Lithium-ion Cells in Battery	N/A

Number of Lithium Metal Cells in Battery	1
Watt Hours Per Battery	2.55
Lithium Content (grams) in Battery	0.33
<b>Mechanical Specifications</b>	
Wall Plate Configurations	Single-Gang
<b>Dimensions</b>	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.813 in
<b>Material Specifications</b>	
Color	Light Almond
Includes Wall Plate	No
<b>Load Ratings</b>	
Resistive Heater	20 A, 120-277 VAC
Tungsten (Incandescent) Range(s)	1800 W, 120 VAC; 1248-1662 W, 208-277 VAC
Ballast Fluorescent	16 A, 120-277 VAC
Electronic Ballast LED	5 A, 120 VAC; 2 A, 277 VAC
DC Loads	4 A, 12 VDC; 2 A, 28 VDC
Motor Load Ratings Ranges	1 HP, 120 VAC; 2 HP, 240 VAC
Max Load Handling Capability	20 A
Inductive Load Ratings Ranges	16 A, 120-277 VAC, 50/60 Hz
<b>Electrical Specifications</b>	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Wiring Configurations	Single; 3-Way
Switch Type	SPST-NO
Neutral Connection Required	No
Hz	50/60
<b>Environmental Specifications</b>	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
<b>Packaging</b>	
Shipping Weight (lbs)	0.472
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in
<b>Standards and Certifications</b>	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

---

## ACCESSORIES



101ST2208A  
ST01A Light Almond Replacement Battery Tray



6ST3057  
ST01 Light Almond Replacement Door