

## Electronic Refrigeration Control - Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 100-240 VAC, Screw Terminals, RS485 (Display and cable sold separately)

Item BIT25-B1S3E-BI



### PRODUCT DESCRIPTION

\*Controller, cable, and display must each be ordered separately. Split Controllers are designed to excel in more demanding applications and provide additional control options for more complex equipment. These controllers can be mounted to a wiring chase or with the refrigeration equipment, eliminating the need for long runs of control wiring.

### FEATURES

- ▶ Remote mounting
- ▶ Remote connectivity
- ▶ Manage multiple alarms
- ▶ Heating or cooling

### APPLICATIONS

- ▶ Ice Refrigeration Machine
- ▶ Reach-In Refrigeration Cooler

### TECHNICAL DATA

#### General

Model Number	BIT25-B1S3E-BI
Description	Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 100-240 VAC, Screw Terminals, RS485 (Display and cable sold separately)
UPC Code	078275150911
Brand	LAE
Country of Origin (Intermatic)	ITALY
Warranty Period	5-Year limited

#### Control Specifications

Minimum Cycle Time	1 min
Mechanism Type	Electrical
Defrost LED Indicator	Red
Has Real-time Clock Face	No
Application Compatibilities	Commercial Refrigeration; Walk-in Cooler; Walk-in Freezer

#### Mechanical Specifications

Mounting Options	DIN
Enclosure Type	IP55 Front
Enclosure Mounting Type	Screw

#### Dimensions

Product Dimensions (H x W x D) in	1.57 x 3.27 x 2.76 in
Panel Opening Height (in)	1.14
Panel Opening Height (mm)	29
Panel Opening Width (in)	2.80
Panel Opening Width (mm)	71
Cut-Out Width (in)	2.80

Cut-Out Width (mm)	71
Cut-Out Height (in)	1.14
Cut-Out Height (mm)	29
Wire Size Max	#10 AWG

### Material Specifications

Color	Black
-------	-------

### Load Ratings

Resistive Load Ratings Ranges Compressor	12 (12) A @ 240 VAC
Resistive Load Ratings Ranges AUX1	16 A @ 240 VAC
Resistive Load Ratings Ranges AUX2	4 A @ 240 VAC

### Electrical Specifications

Wiring Option	Screw terminal block
Input Voltage Range(s)	230 VAC $\pm 10\%$ , 50/60 Hz
Number of Circuits Controlled	3
Electrical Life	100,000 operations at full load
Relay Type Compressor	SPST
Relay Type AUX1	SPST
Relay Type AUX2	SPST
Hz	50/60

### Display and Format

Clock Display Types	LED
---------------------	-----

### Packaging

Shipping Weight (lbs)	0.7
Unit Carton Dimensions (H x W x L) in	2.8 x 3.6 x 4.8 in
Product Weight (lbs)	0.64
Product Weight (kg)	0.29

### Environmental Specifications

Storage Temperature Min (°F)	14
Storage Temperature Max (°F)	122
Storage Temperature Min (°C)	-10
Storage Temperature Max (°C)	50
Operating Humidity	0-80% RH, Non-condensing
Temperature (operation)	14 °F to 122 °F / (-10 °C to 50 °C)

### Standards and Certifications

RoHS Directive	2011/65/EU.
UL Certification	UL60730-1
Other Certifications and Compatibilities	Title 24 LAE; NSF; Green Energy
UL File Number	#SA32385
California Proposition 65	None

RoHS Certification

Y

**ACCESSORIES**

SN4B50P1

Temperature Probe, NTC 10k probe, 5.0 m,  
Gray



SN4B30P1

Temperature Probe, NTC 10k probe, 3.0 m,  
Gray



SN4B20P1

Temperature Probe, NTC 10k probe, 2.0 m,  
Gray



SN4B20P2-B

Temperature Probe, NTC 10k probe, 2.0 m,  
Blue



SN4B20P3-Y

Temperature Probe, NTC 10k probe, 2.0 m,  
Yellow



SN4B30P2-B

Temperature Probe, NTC 10k probe, 3.0 m,  
Blue



SN4B30P3-Y

Temperature Probe, NTC 10k probe, 3.0 m,  
Yellow



SN4B50P2-B

Temperature Probe, NTC 10k probe, 5.0 m,  
Blue



SN4B50P3-Y

Temperature Probe, NTC 10k probe, 5.0 m,  
Yellow



LCD-5S-1I

Display, BIT25