

Electronic Refrigeration Control - Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 230 VAC, Screw Terminals

Item AT2-5BS4E-GI



PRODUCT DESCRIPTION

Panel-Mount Controllers are compact and capable and provide excellent control options in a small package. These models are economical solutions for medium-temperature and low-temperature refrigerated cases, as well as standalone refrigerated display cases.

FEATURES

- Compact
- Manage multiple alarms
- Heating or cooling

APPLICATIONS

- Ice Refrigeration Machine
- Reach-In Refrigeration Cooler

TECHNICAL DATA

General

Model Number	AT2-5BS4E-GI
Description	Refrigeration Controller, 2 NTC/PTC Sensors, 1 Digital Input, 230 VAC, Screw Terminals
UPC Code	078275150867
Brand	LAE
Country of Origin (Intermatic)	ITALY
Warranty Period	5-Year limited

Control Specifications

Minimum Cycle Time	1 min
Mechanism Type	Electrical
Defrost LED Indicator	Red
Has Real-time Clock Face	No
Application Compatibilities	Commercial Refrigeration; Walk-in Cooler; Walk-in Freezer

Mechanical Specifications

Mounting Options	Panel
Enclosure Type	IP55 Front

Dimensions

Mounting Depth (mm)	70
Mounting Depth (in)	2.76
Product Dimensions (H x W x D) in	1.34 x 2.76 x 2.76 in
Panel Opening Height (in)	1.14
Panel Opening Height (mm)	29
Panel Opening Width (in)	2.80
Panel Opening Width (mm)	71
Cut-Out Width (in)	2.80

Cut-Out Width (mm)	71
Cut-Out Height (in)	1.14
Cut-Out Height (mm)	29
Wire Size Max	#10 AWG

Material Specifications

Color	Black
-------	-------

Load Ratings

Resistive Load Ratings Ranges Compressor	16 (5) A @ 240 VAC
Resistive Load Ratings Ranges Fan	7 (2) A @ 240 VAC
Resistive Load Ratings Ranges AUX1	7 (2) A @ 240 VAC

Electrical Specifications

Wiring Option	Screw terminal block
Input Voltage Range(s)	230 VAC $\pm 10\%$, 50/60 Hz
Number of Circuits Controlled	3
Electrical Life	100,000 operations at full load
Relay Type Compressor	SPST
Relay Type Fan	SPST
Relay Type AUX1	SPST
Hz	50/60

Display and Format

Clock Display Types	LED
---------------------	-----

Packaging

Shipping Weight (lbs)	0.48
Unit Carton Dimensions (H x W x L) in	2.5 x 3.2 x 3.6 in
Product Weight (lbs)	0.46
Product Weight (kg)	0.21

Environmental Specifications

Storage Temperature Min (°F)	14
Storage Temperature Max (°F)	122
Storage Temperature Min (°C)	-10
Storage Temperature Max (°C)	50
Operating Humidity	0-80% RH, Non-condensing
Temperature (operation)	14 °F to 122 °F / (-10 °C to 50 °C)

Standards and Certifications

RoHS Directive	2011/65/EU.
UL Certification	UL60730-1
Other Certifications and Compatibilities	Title 24 LAE; Green Energy
UL File Number	#SA32385
California Proposition 65	Lead; DEHP; Nickel

RoHS Certification

Y

ACCESSORIES

SN4B50P1

Temperature Probe, NTC 10k probe, 5.0 m,
Gray



SN4B30P1

Temperature Probe, NTC 10k probe, 3.0 m,
Gray



SN4B20P1

Temperature Probe, NTC 10k probe, 2.0 m,
Gray



SN4B20P2-B

Temperature Probe, NTC 10k probe, 2.0 m,
Blue



SN4B20P3-Y

Temperature Probe, NTC 10k probe, 2.0 m,
Yellow



SN4B30P2-B

Temperature Probe, NTC 10k probe, 3.0 m,
Blue



SN4B30P3-Y

Temperature Probe, NTC 10k probe, 3.0 m,
Yellow



SN4B50P2-B

Temperature Probe, NTC 10k probe, 5.0 m,
Blue



SN4B50P3-Y

Temperature Probe, NTC 10k probe, 5.0 m,
Yellow



LCD-5S-11

Display, BIT25