

Photocontrol - Stem Mount Thermal Photocontrol, 208-277 V, Mexico Sales Only

Item K4123CMX



PRODUCT DESCRIPTION

These photocontrols install on standard outdoor light fixtures and electrical boxes with 1/2"-14 NPSM thread or 7/8" knock-out holes for dusk-to-dawn ON/OFF control of outdoor lighting.

FEATURES

- Mechanical bimetal switch with Cadmium Sulfide photocell
- Delay feature prevents unwanted OFF switching
- Gray plastic housing
- 1/2"-14 NPSM threaded stem
- Washer gasket and locking nut included
- #18 AWG, 9" wire leads

APPLICATIONS

- Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	K4123CMX
Description	Stem Mount Thermal Photocontrol, 208-277 V, Mexico Sales Only
UPC Code	078275029590
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications

Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc
Photocontrol Type	Thermal
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Stem Mount
Photocontrol Sensor Location	Side

Dimensions

Product Height (in)	3
Product Height (mm)	76.2
Product Width (in)	1.563
Product Width (mm)	39.7
Product Depth (in)	1.563
Product Depth (mm)	39.7
Wire Lead Length (in)	9

Wire Lead Length (mm)	228.6
Wire Size Max	#18 AWG
Material Specifications	
Color	Gray
Housing Material	Polycarbonate
Load Ratings	
Magnetic Ballast Range(s)	8.3 A, 1700-2300 VA
Tungsten Range(s)	15 A, 3100-4150 W
Electrical Specifications	
Wiring Option	Wire leads
Input Voltage Range(s)	208-277 VAC, 50/60 Hz
Hz	50/60
Packaging	
Shipping Weight (lbs)	0.241
Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in
Operating Specifications	
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Environmental Specifications	
Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
Usage Environments	Outdoor
Standards and Certifications	
UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; NOM
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



K42-SW-A

Swivel Arm Accessory for EK4136S, K4100 Series Stem Mount Photocontrols



22LG116

Light Guard Accessory for K4100 Series, K4200 Series Thermal Photocontrols



6LV1352

Light Shield Accessory for EK4036S, EK4436SM, K4000 Series Button Photocontrols