

In-Wall Timer - Spring Wound Countdown Timer, Mechanism Only, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, Without Hold

Item FF12H10



PRODUCT DESCRIPTION

The FF Series Commercial Countdown Timers are designed to replace any standard wall switch and do not require electricity to operate. These energy-efficient switches automatically limit the ON times for fans, lighting, motors, heaters, and other energy consuming loads. A commercial "brushed metal" look plate (plastic construction) meets NEC requirements. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Mechanism only
- 12-Hour timer
- SPST (Single-Pole Single-Throw)
- Breaks circuit at end of timing cycle
- No electricity required to operate
- Replaces any standard or decorator single-gang wall switch
- Automatically limits ON time for energy consuming loads
- Quick and easy installation
- Time-saving up front terminal connection with teeter-type terminals
- Brushed metal look switch plate meets NEC requirements (plate is included)

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Motor Control
- Air Movement & Ventilation

TECHNICAL DATA

General

Model Number

FF12H10

Description

Spring Wound Countdown Timer, Mechanism Only, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, Without Hold

UPC Code

078275123694

Brand

Intermatic

Country of Origin (Intermatic)

TUNISIA

Warranty Period

1-Year limited

Control Specifications

Hold Mode Included

No

Material Specifications

Color

Black

Finish

Brushed Metal

Load Ratings

Resistive Heater

20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC

Tungsten (Incandescent) Range(s)

7 A, 125 VAC, 50/60 Hz, 875 W

Motor Load Ratings Ranges

1 HP, 125 VAC; 2 HP, 250 VAC

Electrical Specifications

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Switch Type	SPST
Neutral Connection Required	No
Hz	50/60

Environmental Specifications

Temperature (operation)	40 - 120 °F / 4 - 49 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.249
Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in

Standards and Certifications

UL Certification	RU
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A