

Mechanical Time Switch - 24-Hour 120V Mechanical Panel Mount Timer with Manual Override, 48 Trippers

Item PB913N66



PRODUCT DESCRIPTION

These timers provide automatic control for pumps, cleaners and other types of loads. Timers have three-way mounting; flush in round opening, raised in rectangular opening or on base. Quick connect terminals for easy installation.

FEATURES

- ▶ Automated control for pumps, cleaners and other types of loads
- ▶ 3 different mounting methods
- ▶ Quick connect terminals for easy installation
- ▶ 24-hour timing cycle - MIN ON time 1-hr, MAX ON time 23-hr, 30-min intervals
- ▶ 7-day timing cycle - 6 to 162-hr ON time, 3-hr intervals

APPLICATIONS

- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

| General                           |   |
|-----------------------------------|---|
| Model Number                      | PB913N66  |
| Description                       | 24-Hour 120V Mechanical Panel Mount Timer with Manual Override, 48 Trippers |
| UPC Code                          | 09999999990   |
| Brand                             | Intermatic  |
| Country of Origin (Intermatic)    | MEXICO  |
| Warranty Period                   | 1-Year limited  |
| Control Specifications            |   |
| Minimum Cycle Time                | 1 hr  |
| Maximum Cycle Time                | 23 hrs  |
| Timing Interval                   | 30 min  |
| Operation Mode                    | 24 hour   |
| Has Manual Override               | Yes   |
| Has Override Switch               | Yes   |
| Mechanical Specifications         |   |
| Captive Trippers                  | 48  |
| Dimensions                        |   |
| Product Dimensions (H x W x D) in | 3.333 x 2.813 x 1.953 in  |
| Load Ratings                      |   |
| Resistive Load Ratings Ranges     | 20 A, 120-277 VAC, 60 Hz  |
| Pilot Duty Load Ratings Ranges    | 360 VA, 120-240 VAC, 60 Hz  |
| Motor Load Ratings Ranges         | 1 HP, 16 FLA @ 120 VAC, 60 Hz; 2 HP, 12 FLA @ 240 VAC, 60 Hz                |
| Electrical Specifications         |   |



|                        |   |
|------------------------|---|
| Wiring Option          | Terminals; (4) 1/4" male (2) for load (2) for independent clock motor |
| Input Voltage Range(s) | 120 VAC, 60 Hz  |
| Number of Circuits     | 1   |
| Switch Type            | SPST  |
| Hz                     | 60  |

|                                       |                    |
|---------------------------------------|--------------------|
| Packaging                             |                    |
| Shipping Weight (lbs)                 | 0.499              |
| Unit Carton Dimensions (H x W x L) in | 4 x 2.75 x 3.59 in |

|  |              |
|--|--------------|
| Standards and Certifications             |              |
| UL Certification                         | RU           |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | None         |
| RoHS Certification                       | N/A          |

ACCESSORIES



156PB10398A  
Trippers - Clip, ON/OFF, 24 Hour for PB and PF1100 Series



107TN221  
Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222  
Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS