

Hour Meter - AC Hour Meter

Item FWZ72-120



PRODUCT DESCRIPTION

The FWZ Series AC Hour Meters are flush panel mountable designed to fit into tight locations. They are non-resettable and flush panel mounted with watertight/dust-tight sealed bezels designed to withstand IP54 environmental rating (with use of a gasket). All models are black plastic (except FWZ72B which is blue-silver on colorless frosted polycarbonate) with white numerals on a black background. Tents and hundredths numerals are yellow.

APPLICATIONS

- Monitoring
- Distribution/Control Panel

TECHNICAL DATA

General

Model Number	FWZ72-120
Description	AC Hour Meter
UPC Code	078275153158
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications

Capacity (Hours)	99999.99
------------------	----------

Mechanical Specifications

Mounting Options	Flush; Panel
Number of Digits (Hours)	5
Number of Digits (Tenths)	2
Bezel Mount Type	3-Hole
Mounting Description	Flush panel retainer mounted (3) 0.185" holes for #8 screws
Gasket Model	G-72U (sold separately)
Mechanical Movement	Synchronous

Dimensions

Mounting Depth (mm)	60.6
Mounting Depth (in)	2.386
Product Diameter (in)	2.2
Product Diameter (mm)	55.8
Panel Opening Diameter (in)	1.75
Panel Opening Diameter (mm)	44.4
Panel Opening Height (in)	1
Panel Opening Height (mm)	24

Panel Opening Width (in)	1.5
Panel Opening Width (mm)	38
Digits Height (mm)	4.1
Digits Height (in)	0.16
Bezel Diameter (in)	2.83
Bezel Diameter (mm)	72

Material Specifications

Color	Black
Digits Coloring (Hours)	White on Black
Digits Coloring (Tenths)	Yellow on Black
Hour Meter Material	Plastic

Electrical Specifications

Maximum Power Consumption (VA)	1
Wiring Option	Combination 1/4" spade and screw clamp; Rear access screw terminals available (Model "K")
Input Voltage Range(s)	24 or 120 VAC

Packaging

Shipping Weight (lbs)	0.16
Unit Carton Dimensions (H x W x L) in	2.56 x 2.83 x 2.83 in

Environmental Specifications

Environmental Rating	IP54 (With Use of Gasket)
Temperature (operation)	-40 °F to 160 °F / (-40 °C to 72 °C)

Standards and Certifications

UL Certification	RU
CSA Certification	cCSAus
Other Certifications and Compatibilities	RU
CSA File Number	151753
RU File Number	#E22587
California Proposition 65	None
RoHS Certification	Y