

In-Wall Timer - Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, White

Item EI400WC



PRODUCT DESCRIPTION

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Programmable countdown time interval from one second to 24 hours
- Settings stored in non-volatile memory
- Optional audible and/or visual warning of impending load switch OFF
- Lockable settings help avoid unintended changes
- Single-pole or 3-way switch compatible installation
- Incandescent/fluorescent/CFL/LED compatible
- Isolated switch allows timer to be used with any load type including AC and DC loads
- Replaceable CR2 lithium battery provides up to three years of operation
- No neutral wire connection enables easy retrofitting and quicker installation
- 24-hour programming allows for continuous operation

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	EI400WC
Description	Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, White
UPC Code	078275101388
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	5-Year limited

Control Specifications

Time Presets	Programmable
Operation Mode	Countdown
Countdown Time	1 sec; 24 hrs
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	CR2
Battery Service Type	Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Lithium Manganese Dioxide (LiMnO ₂)
Number of Batteries Included	1
Battery Weight (grams)	11
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	1
Watt Hours Per Battery	3.0

Lithium Content (grams) in Battery 0.5

Mechanical Specifications

Wall Plate Configurations Single-Gang

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.188 in

Material Specifications

Color White

Load Ratings

Resistive Heater 20 A, 2400-5540 W, 120-277 VAC

Tungsten (Incandescent) Range(s) 1800 W, 120 VAC; 1248-1662 W, 208-277 VAC

DC Loads 4 A, 12 VDC; 2 A, 28 VDC

Motor Load Ratings Ranges 1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz

Inductive Load Ratings Ranges 16 A, 120-277 VAC, 50/60 Hz

Electrical Specifications

Input Voltage Range(s) 120-277 VAC, 50/60 Hz

Wiring Configurations Single; 3-Way

Switch Type SPST

Hz 50/60

Environmental Specifications

Temperature (operation) 32 - 122 °F / 0 - 50 °C

Packaging

Shipping Weight (lbs) 0.399

Unit Carton Dimensions (H x W x D) in 4.88 x 3 x 2.13 in

Standards and Certifications

CSA Certification cCSAus

Other Certifications and Compatibilities Green Energy

California Proposition 65 DEHP

RoHS Certification N/A