

In-Wall Timer - 7-Day Standard Programmable Timer, 125 VAC, 15A, Ivory

Item EI500C



PRODUCT DESCRIPTION

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- 7-day programmable schedules with 14 ON/OFF events
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- Single-pole circuit
- Incandescent/fluorescent/CFL/LED compatible
- Built-in rechargeable, non-serviceable battery backup
- Requires neutral connection
- Backlit LCD display
- Decorator switch plate not included

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation
- Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	EI500C
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, Ivory
UPC Code	078275105218
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24 hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Service Type	Non-Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Ni-MH
Number of Batteries Included	1
Battery Weight (grams)	3.5
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	N/A
Watt Hours Per Battery	0.096
Lithium Content (grams) in Battery	N/A

Mechanical Specifications

Wall Plate Configurations

Single-Gang

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.438 in

Material Specifications

Color Ivory
Includes Wall Plate Yes

Load Ratings

General Purpose 15 A, 125 VAC, 60 Hz
Resistive Heater 15 A, 1875 W
Tungsten (Incandescent) Range(s) 1000 W
Ballast Fluorescent 8 A, 1000 VA
Electronic Ballast LED 4 A, 500 VA
Motor Load Ratings Ranges 1/4 HP, 125 VAC, 60 Hz
Inductive Load Ratings Ranges 1000 VA, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s) 125 VAC, 60 Hz
Wiring Configurations Single
Neutral Connection Required Yes
Hz 60

Environmental Specifications

Temperature (operation) 32 - 104 °F / 0 - 40 °C

Packaging

Shipping Weight (lbs) 0.351
Unit Carton Dimensions (H x W x D) in 4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification cULus
Other Certifications and Compatibilities Green Energy
California Proposition 65 DEHP
RoHS Certification N/A