

In-Wall Timer - Long-Range Wireless Switch with Remote Control Fob Bundle

Item RC-LRSK1-WH



PRODUCT DESCRIPTION

The Long-Range Wireless Switch with Remote Control Fob is designed for use with Intermatic pool and spa panels, Intermatic weatherproof covers, and similar weather-rated NEMA 3R enclosures. Featuring 915 MHz spread spectrum wireless technology, the switch communicates with the included remote control fob at distances up to 400 feet through metal panels, with no external antenna required. The internal components of the Long-Range Wireless Switch have been treated with a special coating to resist oxidation in outdoor environments and supports an operating temperature range of -30° C to 70° C (-22° F to 158° F), while the fob supports an operating temperature range of 0° C to 50° C (32° F to 122° F).

FEATURES

- Convenient all-in-one package contains everything you need to control pool lights and other outdoor lighting up to 400 feet away.
- Ruggedized switch for long life and enhanced reliability in NEMA 3R outdoor enclosures.
- 915 MHz wireless technology provides extended range and remarkable performance, even through metal panels.
- Switch has operating temperature range of -30° C to 70° C (-22° F to 158° F), while fob has an operating temperature range of 0° C to 50° C (32° F to 122° F).
- Includes both the Long-Range Switch (RC-LRS1-WH) and the Remote Control Fob (RC-LRSR-WH) in a single convenient kit.
- Box Contents: (1) long-range wireless switch, (1) faceplate (2) faceplate mounting screws, (2) electrical box screws, (4) wire connectors, (1) remote control fob, (2) AAA batteries, installed (1) wall bracket, (2) wall bracket screws, (1) visor clip, (2) quick installation guides.

APPLICATIONS

- Landscape Lighting
- Pool Lighting Control

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | RC-LRSK1-WH |
| Description | Long-Range Wireless Switch with Remote Control Fob Bundle |
| UPC Code | 078275158931 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|--|--------------------------------------|
| Data Transfer Options | Long-range 915 MHz; Remote Operation |
| Operation Mode | On/Off |
| Battery Type | AAA |
| Battery Service Type | Replaceable |
| Battery life | Up to 10 years |
| Wireless Signal Range Ft | 400 |
| Chemical Composition of the Battery Cell | Alkaline |
| Number of Batteries Included | 2 |

Material Specifications

| | |
|-------|-------|
| Color | White |
|-------|-------|

Load Ratings

| | |
|------------------------|-------|
| General Purpose | 5 A |
| Electronic Ballast LED | 600 W |
| Tungsten Load Ratings | 600 W |

Electrical Specifications

| | |
|------------------------|-----------------------|
| Input Voltage Range(s) | 120 VAC, 60 Hz; 3 VDC |
| Hz | 60 |

Environmental Specifications

| | |
|-------------------------|----------------------------|
| Temperature (operation) | -22 - 158 °F / -30 - 70 °C |
|-------------------------|----------------------------|

Packaging

| | |
|---------------------------------------|----------------------|
| Shipping Weight (lbs) | 0.6 |
| Unit Carton Dimensions (H x W x D) in | 5 x 2.938 x 2.969 in |

Standards and Certifications

| | |
|--|---|
| Other Certifications and Compatibilities | cETLus; FCC; IC: 29501-3604; Green Energy |
| California Proposition 65 | None |
| RoHS Certification | N |
| CA Prop 65 Message | This product is in compliance with Prop65 |
| PDF Standards And Certifications | Green Energy; FCC; cETLus |
| Epi Certifications | cETLus; FCC; Green Energy |

URL's

| | |
|-----------------------|--|
| Software DownLoad URL | View FAQs |
|-----------------------|--|