

Sensor - Dual Tech Ceiling Mount OCC/VAC Sensor

Item ALC-CMP-DT-BT



PRODUCT DESCRIPTION

The ALC-CMP-DT-BT is a Dual-Technology (PIR and Ultrasonic) Sensor designed for use with the ARISTA® Lighting Controls System by Intermatic and will control lighting based upon occupancy/vacancy. If space is configured for Occupancy and movement is detected, the sensor informs the ARISTA controller(s) in the space and the lights will illuminate. The lights will turn off after the ARISTA controller(s) deem the space vacant and the timeout period completes. If space is configured for Vacancy, the ARISTA controller(s) in the space will only react when they are manually activated. The lights will turn off after the ALC-CMP-DT-BT deems the space vacant and the timeout period completes. This sensor provides a 360° coverage pattern, PIR Coverage - Up to 1300 ft² - US Coverage - Up to 1600 ft². Pricing is available upon request.

FEATURES

- Wired or wireless communications.
- Toolless battery replacement.
- Multiple mounting options.
- Adjustable sensitivity settings.
- Independent settings for Ultrasonic and PIR sensor technologies.
- Adjustable time-out settings.

APPLICATIONS

- Indoor Lighting Control
- Indoor Sensing Control

TECHNICAL DATA

General

Model Number	ALC-CMP-DT-BT
Description	Dual Tech Ceiling Mount OCC/VAC Sensor
UPC Code	078275150720
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	CHINA

Control Specifications

Operation Features	Presence
Operation Mode	Occupancy; Vacancy
Data Transfer Options	Bluetooth; Wired
Backup Restoration Time	1 Minute
Backup Type	Non-volatile
Backup Protection Time	Indefinite
PIR Coverage Area (sq ft)	1300
Ultrasonic Coverage Area (sq ft)	1600
Application Compatibilities	ARISTA Controllers
Function type	Occupancy; Scheduled ON/OFF; Vacancy

Mechanical Specifications

Mount Type	Ceiling
------------	---------

Dimensions

Product Height (in)	4.53
---------------------	------

Product Height (mm)	115.062
Product Width (in)	4.53
Product Width (mm)	115.062
Product Depth (in)	2.95
Product Depth (mm)	74.93
Class 2 Wire Size Min	22
Class 2 Wire Size Max	16
Material Specifications	
Color	White
Material	Plastic
Communication Method	
Radio signal	Bluetooth
Electrical Specifications	
Input Voltage Range(s)	24 VDC
Wiring Options Low Voltage	Terminals
Display and Format	
Status Indicator	LED Indicator
Packaging	
Shipping Weight (lbs)	0.525
Shipping Weight (kg)	0.238
Product Weight (lbs)	0.525
Product Weight (kg)	0.238
Operating Specifications	
Programming Targets	Smartphone
Tampering protection	Yes
Environmental Specifications	
Operating Humidity	Dry Location
Temperature (operation)	32°F..131°F
Temperature (operation)	0°C..55°C
Usage Environments	Indoor
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	ASHRAE 90.1 2016; IECC 2018; Green Energy +
California Proposition 65	None
RoHS Certification	Y