

## Occupancy Sensor - Residential In-Wall PIR Vacancy Sensor, White

Item IOS-DPBV-WH



### PRODUCT DESCRIPTION

The passive infrared sensors work by detecting the difference between heat emitted from the human body in motion and the background space. Once the sensor switch is manually turned ON, it can turn a load ON and hold it as long as the sensor detects any motion. After no motion is detected for the set time delay, the load is turned OFF automatically. The sensor switch has one relay (equal to single pole switch); no minimum load requirements.

### FEATURES

- Passive Infrared (PIR) sensing for presence detection
- Adjustable PIR sensitivity
- Adjustable time delay 15 sec to 30 min
- Adjustable ambient light sensor override for occupancy switch models
- Coverage: 180°, 700 ft<sup>2</sup> with non-obstructed views
- IOS-DPBIF and IOS-DPBV models are Incandescent/Fluorescent/CFL/LED compatible and require a neutral connection
- 'No neutral' models offered for retrofit applications
- Fits standard decorator wall plate (included)
- Automatic OFF after time delay expires with manual "OFF" option
- Meets California Title 20 Requirements

### APPLICATIONS

- Indoor Sensing Control

### TECHNICAL DATA

#### General

Model Number	IOS-DPBV-WH
Description	Residential In-Wall PIR Vacancy Sensor, White
UPC Code	078275149076
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA

#### Control Specifications

Sensor Switch Type	Vacancy
Sensor Technology	PIR (Passive Infrared); Zero-crossing
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	20 min
Adjustable Light Level Min	25 fc
Adjustable Light Level Max	Daylight
PIR Coverage Area (sq ft)	980
Application Compatibilities	CFL; Fluorescent; Incandescent

#### Mechanical Specifications

PIR Coverage Pattern (degrees)	180
Maximum Mounting Height (ft)	4 ft
Mount Type	In-Wall

#### Dimensions

Product Height (in)	2.75
Product Height (mm)	70
Product Width (in)	1.456
Product Width (mm)	37
Product Depth (in)	1.625
Product Depth (mm)	41

**Material Specifications**

Color	White
Includes Wall Plate	Yes

**Load Ratings**

Tungsten Range(s)	800 W
Resistive Load Ratings Ranges	5 A
Motor Load Ratings Ranges	1/4 HP
Electronic Ballast Load Ratings Ranges	800 VA

**Electrical Specifications**

Input Voltage Range(s)	120 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Hz	60

**Packaging**

Shipping Weight (lbs)	0.3
Shipping Weight (kg)	0.136
Unit Carton Dimensions (H x W x L) in	4.9 x 3 x 2.25 in

**Environmental Specifications**

Temperature (operation)	32 - 131°F / 0 - 55°C
-------------------------	-----------------------

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	None
RoHS Certification	N/A