

## Hour Meter - AC Hour Meter

Item FWZ55K-120U



## TECHNICAL DATA

### General

|                                |                     |
|--------------------------------|---------------------|
| Model Number                   | FWZ55K-120U         |
| Description                    | AC Hour Meter       |
| UPC Code                       | 078275153134        |
| Brand                          | Domestic Intermatic |
| Country of Origin (Intermatic) | MEXICO              |
| Warranty Period                | 1-Year limited      |

### Control Specifications

|                  |          |
|------------------|----------|
| Capacity (Hours) | 99999.99 |
|------------------|----------|

### Mechanical Specifications

|                           |   |
|---------------------------|---|
| Mounting Options          | Flush; Panel  |
| Number of Digits (Hours)  | 5   |
| Number of Digits (Tenths) | 2   |
| Mounting Description      | Flush panel retainer mounted with slip-on retaining bracket |
| Gasket Model              | G-55U (sold separately)                                     |
| Mechanical Movement       | Synchronous   |

### Dimensions

|                                   |                       |
|-----------------------------------|-----------------------|
| Mounting Depth (mm)               | 59.2                  |
| Mounting Depth (in)               | 2.33                  |
| Product Dimensions (H x W x D) in | 1.18 x 2.17 x 2.05 in |
| Panel Opening Height (in)         | 1.08                  |
| Panel Opening Height (mm)         | 27.5                  |
| Panel Opening Width (in)          | 2.06                  |
| Panel Opening Width (mm)          | 52                    |
| Digits Height (mm)                | 4.1                   |
| Digits Height (in)                | 0.16                  |

|                   |      |
|-------------------|------|
| Bezel Width (mm)  | 60   |
| Bezel Height (mm) | 30   |
| Bezel Width (in)  | 2.17 |
| Bezel Height (in) | 1.18 |

#### Material Specifications

|                          |                 |
|--------------------------|-----------------|
| Color                    | Black           |
| Digits Coloring (Hours)  | White on Black  |
| Digits Coloring (Tenths) | Yellow on Black |
| Hour Meter Material      | Plastic         |

#### Electrical Specifications

|                                |   |
|--------------------------------|---|
| Maximum Power Consumption (VA) | 1   |
| Wiring Option                  | Combination 1/4" spade and screw clamp; Rear access screw terminals available (Model "K") |
| Input Voltage Range(s)         | 120 VAC, 60 Hz  |
| Hz                             | 60  |

#### Packaging

|                                       |                       |
|---------------------------------------|-----------------------|
| Shipping Weight (lbs)                 | 0.19                  |
| Unit Carton Dimensions (H x W x L) in | 2.25 x 3.25 x 3.25 in |

#### Environmental Specifications

|                         |                                      |
|-------------------------|--------------------------------------|
| Environmental Rating    | IP54 (With Use of Gasket)            |
| Temperature (operation) | -40 °F to 160 °F / (-40 °C to 72 °C) |

#### Standards and Certifications

|                           |         |
|---------------------------|---------|
| UL Certification          | cRUs    |
| CSA Certification         | cCSAus  |
| RU File Number            | #E22587 |
| California Proposition 65 | None    |
| RoHS Certification        | Y       |