

Hour Meter - AC Hour Meter

Item FWZ72B-120U



PRODUCT DESCRIPTION

The FWZ Series AC Hour Meters are flush panel mountable designed to fit into tight locations. They are non-resettable and flush panel mounted with watertight/dust-tight sealed bezels designed to withstand IP54 environmental rating (with use of a gasket). All models are black plastic (except FWZ72B which is blue-silver on colorless frosted polycarbonate) with white numerals on a black background. Tenths and hundredths numerals are yellow.

APPLICATIONS

- ▶ Monitoring
- ▶ Distribution/Control Panel

TECHNICAL DATA

General	
Model Number	FWZ72B-120U
Description	AC Hour Meter
UPC Code	078275153189
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Capacity (Hours)	99999.99
Mechanical Specifications	
Mounting Options	Flush; Panel
Number of Digits (Hours)	5
Number of Digits (Tenths)	2
Bezel Mount Type	3-Hole
Mounting Description	Flush panel retainer mounted (3) 0.185" holes for #8 screws
Gasket Model	G-72U (sold separately)
Mechanical Movement	Synchronous
Dimensions	
Mounting Depth (mm)	60.6
Mounting Depth (in)	2.386
Product Diameter (in)	2.2
Product Diameter (mm)	55.8
Panel Opening Diameter (in)	1.75
Panel Opening Diameter (mm)	44.4
Panel Opening Height (in)	1
Panel Opening Height (mm)	24

Panel Opening Width (in)	1.5
Panel Opening Width (mm)	38
Digits Height (mm)	4.1
Digits Height (in)	0.16
Bezel Diameter (in)	2.83
Bezel Diameter (mm)	72

Material Specifications	
Color	Blue and Silver on Frosted Clear
Digits Coloring (Hours)	White on Black
Digits Coloring (Tenths)	Yellow on Black
Hour Meter Material	Polycarbonate

Electrical Specifications	
Maximum Power Consumption (VA)	1
Wiring Option	Combination 1/4" spade and screw clamp; Rear access screw terminals available (Model "K")
Input Voltage Range(s)	120 or 240 VAC

Packaging	
Shipping Weight (lbs)	0.22
Unit Carton Dimensions (H x W x L) in	3.25 x 3.25 x 4.75 in

Environmental Specifications	
Environmental Rating	IP54 (With Use of Gasket)
Temperature (operation)	-40 °F to 160 °F / (-40 °C to 72 °C)

Standards and Certifications	
UL Certification	cRUus
CSA Certification	cCSAus
RU File Number	#E22587
California Proposition 65	None
RoHS Certification	Y