

Salt Chlorinators - Salt chlorinator system (1.15 lbs/24 hr) includes power center, 25K cell, nuts/tails, flow switch, and acid cleaning kit

Item SCG25K



PRODUCT DESCRIPTION

Intermatic salt chlorine generators provide the most popular form of chlorination. This system converts sodium chloride (salt) to sodium hypochlorite (liquid chlorine) through a process of electrolysis to neutralize any germs in the pool. With Intermatic's I-Pure, you can rest assured your pool and spa water is always crystal clear, fresh and clean.

FEATURES

- ▶ Power saving technology that incorporates a built in self-regulator for high salt, allowing for greater efficiency.
- ▶ Smart, self-cleaning cell electrode with adjustable cleaning cycles.
- ▶ Premium grade quick-connect, self-cleaning titanium cell for increased life span.
- ▶ Modern, compact power pack, isolation transformer design and IP34 ingress protection.
- ▶ Internal over temperature protection and trip indication.
- ▶ Easy installation, simple setup and operation for new or existing pools.
- ▶ Quick-connect cell with horizontal or vertical installation.
- ▶ Acrylic weather shield, flow switch, cleaning cap, mounting bracket, wall anchors, and screws provided.
- ▶ Efficient chlorine production: the chlorinator cell supports water temperature ranges between 50 F and 104 F (10 C and 40 C.)
- ▶ Real-time data for easy monitoring.

APPLICATIONS

- ▶ Salt Chlorine Generators
- ▶ Inground Pools

TECHNICAL DATA

General

Model Number	SCG25K
Description	Salt chlorinator system (1.15 lbs/24 hr) includes power center, 25K cell, nuts/tails, flow switch, and acid cleaning kit
UPC Code	078275159013
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	2-Year limited

Mechanical Specifications

Mounting Options	Bracket; Post with Flat Panel
Cell Installation Direction	Vertical or Horizontal

Dimensions

Product Dimensions (H x W x D) in	6.06 x 9.81 x 7.24 in
-----------------------------------	-----------------------

Material Specifications

Color	Gray power center, clear body, white end caps
-------	---

Electrical Specifications

Input Voltage Range(s)	0.7-1.4 A, 115/230 VAC, 50/60 Hz
Neutral Connection Required	Yes

Polarity Reversing Times 4 to 10 Hours

Packaging

Shipping Weight (lbs)	0.01
Unit Carton Dimensions (H x W x L) in	7.795 x 15.551 x 16.339 in

Operating Specifications

Ideal for Pools Up to (Gallons)	25,000
---------------------------------	--------

Environmental Specifications

Temperature (operation)	50 °F to 104 °F / (10 °C to 40 °C)
-------------------------	------------------------------------

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP

ACCESSORIES

SCG1000
Nut/Tail/O-ring Kit (Qty 2 of each)



SCG1200-1
Complete Flow Switch R1P2 with Faucet Tee and Silicone Seal



SCG1490
Cell Cleaning Kit



SCGCELL25K
Replacement Cell for SCG25K system (1.15Lb/24hr - 13 Plates, 2.1"). Includes nuts, tails, and O-rings.



SCGCELLDBH
Intermatic SCG Dummy Bypass Cell Housing



SCGORING
O-Ring replacement (Qty 2 in ziplock)



SCGPWR15K-60K
Intermatic SCG15K-60K - Replacement Power Center ONLY - USA UL