

## Surge Protection Device - Surge Protective Device, 240 VAC 1Ph w/Green Ground Lead, Type 1 or Type 2, Outdoor, Connected Equipment Warranty 3yr \$7,500

Item AG3000G



### PRODUCT DESCRIPTION

Power surges are the silent killer for home appliances and HVAC equipment. Most homeowners protect their electronics but leave more valued equipment unprotected. Surges can wipe out equipment and leave you searching for answers. Search no more. The easy-to-install AG3000G Surge Protective Device (SPD) is the perfect add-on for HVAC equipment. A green LED indicator will be on when the SPD is operating correctly. A red LED indicator will be on when protection is diminished, and the SPD needs to be replaced. Trusted, state-of-the-art TPMOV® (Thermally Protected Metal Oxide Varistor) technology eliminates the potentially hazardous failure modes commonly associated with standard MOV technology. UL Listed to ANSI/UL 1449, 5th Edition.

### FEATURES

- Modes of protection: L-G, L1-L2
- TPMOV® surge protection technology
- LED Indicators. Green: unit operating correctly Red: protection diminished, replace unit.
- Green grounding lead
- Type 4X watertight and UV resistant plastic enclosure
- 3-year product warranty
- \$7,500 connected equipment warranty for 3 years
- UL certified to ANSI/UL 1449 5th edition

### APPLICATIONS

- Distribution Panel
- Service Entrance
- HVAC Equipment Protection

### TECHNICAL DATA

#### General

Model Number	AG3000G
Description	Surge Protective Device, 240 VAC 1Ph w/Green Ground Lead, Type 1 or Type 2, Outdoor, Connected Equipment Warranty 3yr \$7,500
UPC Code	078275157682
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	3-Year limited
Connected Equipment Warranty Period	3-Year
Connected Equipment Warranty Coverage (USD)	7500

#### Electrical Specifications

Modes of Protection	L-G, L1-L2
Short Circuit Current Rating	100 kA
Nominal Discharge Current	20 kA
Maximum Surge Current Rating Per Phase	50 kA
Surge Protection Technology	TPMOV®
Maximum Continuous Operating Voltage (L-G)	150
Maximum Continuous Operating Voltage (L-L)	300
Voltage Protection Rating (L-L)	1200
Voltage Protection Rating (L1-N/G)	700
Phase	Single

Voltage 208/240 VAC Single-Phase

#### Control Specifications

Surge Protection Type	1; 2
Surge Protection LED Indicator	Green; Red

#### Mechanical Specifications

Number of Wire Leads	3
Enclosure Type	Indoor/outdoor type 4X

#### Dimensions

Product Dimensions (H x W x D) in	3.875 x 1.625 x 4.188 in
Wire Lead Length (in)	18
Wire Size Max	#10 AWG, Tinned Copper

#### Packaging

Shipping Weight (lbs)	0.65
Unit Carton Dimensions (H x W x L) in	4.5 x 2 x 4.25 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	HVACR; Green Energy
UL Standard	ANSI/UL 1449 5th Edition
California Proposition 65	DEHP
RoHS Certification	N/A