

Pool Pumps - 1.5 HP 2-Speed Pool Pump, On/Off Switch, 3 ft Cord, Twistlock Plug

Item APAP152SP3T



PRODUCT DESCRIPTION

The Intermatic PURFLO two-speed DOE compliant pool pumps featuring a rugged TEFC motor, meets all the needs for todays energy conscious pool owners. PURFLO is built to stand up to the most demanding installations and conditions. Meanwhile, the TEFC motor design prevents water, dust and other contaminants from entering and affecting the motor's operation and longevity.

FEATURES

- ▶ Now with a 2-year limited warranty on parts (Effective May 1, 2025)
- ▶ Totally enclosed fan-cooled (TEFC) pool pump technology.
- ▶ Self-priming for faster, easier start up.
- ▶ Energy-efficient 2-speed motor. Uses half the amps on low speed, saving 50% on electricity costs.
- ▶ Quad seal motor design with layers of protection built in to ensure long pump life.
- ▶ Large strainer basket with see-thru lid.
- ▶ Integrated On/Off switch. DOE Compliant.
- ▶ Ultra-Quiet for installation near bedrooms & windows.
- ▶ 3 ft. cord with standard plug.
- ▶ Drain valve for easy maintenance.

APPLICATIONS

- ▶ Above Ground Pools

TECHNICAL DATA

| General | |
|---------------------------------------|--|
| Model Number | APAP152SP3T |
| Description | 1.5 HP 2-Speed Pool Pump, On/Off Switch, 3 ft Cord, Twistlock Plug |
| UPC Code | 816965015559 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 2-Year limited |
| Dimensions | |
| Cord Length (ft) | 3' Cord with Twistlock Plug |
| Material Specifications | |
| Color | Black |
| UV Resiliant Outdoor Enclosure | Yes |
| Electrical Specifications | |
| Input Voltage Range(s) | 115 VAC |
| HP | 1 1/2 |
| Packaging | |
| Shipping Weight (lbs) | 27.1 |
| Unit Carton Dimensions (H x W x L) in | 10.87 x 8.66 x 23.2 in |
| Unit Package Quantity | 1 |
| Operating Specifications | |



| | |
|---|------|
| Min RPM | 1725 |
| Max RPM | 3450 |
| GPM | 90 |
| DOE - WEF Rating (Weighted Energy Factor) | 5.5 |
| Operating Current (Low speed) | 3.5 |
| Operating Current (High speed) | 8.5 |
| Freeze Protection | No |
| DOE Compliant | Yes |
| Self Priming | Yes |

Standards and Certifications

| | |
|--|--------|
| Other Certifications and Compatibilities | cETLus |
| California Proposition 65 | Lead |
| RoHS Certification | N |