

Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White

Item IOS-CMP-U



PRODUCT DESCRIPTION

The IOS-CMP-U 360° Passive Infrared (PIR) Line Voltage Occupancy Sensors control lighting systems based on occupancy and ambient light levels. When movement is detected, the sensor turns the lights ON. If no movement is detected for a user-specified time, the lights are turned OFF. The occupancy sensor provides a 360° coverage pattern, up to 1200 square feet.

FEATURES

- ▶ PIR technology sensing for presence detection
- ▶ Coverage: 1200 ft² when mounted on 8 to 11 ft ceiling
- ▶ Zero-crossing technology for long life and performance
- ▶ Adjustable ambient light sensor override
- ▶ Requires neutral connection
- ▶ Incandescent/Fluorescent/CFL/LED compatible

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

General

Model Number	IOS-CMP-U
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White
UPC Code	078275139916
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA

Control Specifications

Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared); Zero-crossing
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	10 fc
Adjustable Light Level Max	150 fc
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Mount Type	Ceiling

Dimensions

Product Height (in)	1.375
Product Height (mm)	35
Product Diameter (in)	4.563

Product Diameter (mm)	116
Material Specifications	
Color	White
Load Ratings	
Tungsten Range(s)	800 W, 120/125 VAC
Resistive Load Ratings Ranges	10 A, 120/125 VAC
Motor Load Ratings Ranges	1/4 HP, 120 VAC
Electronic Ballast Load Ratings Ranges	800 VA, 120/125 VAC; 1600 VA, 277 VAC
Electrical Specifications	
Input Voltage Range(s)	120/277 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Watts	800
Hz	60
Amperage	20 A
Packaging	
Shipping Weight (lbs)	0.399
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	2 x 5 x 5 in
Environmental Specifications	
Temperature (operation)	32 - 131°F / 0 - 55°C
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	None
RoHS Certification	N/A