

Weatherproof Cover - Low-Profile Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hz, Black

Item WP6000BL



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- 100% Paintable surface.
- Complies with 2020 NEC Article 314.15 for wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws.
- Lockable hasp: All models accept up to 0.19" dia shank.
- Impact rated: 12 lbf. impact test to ensure cover remains intact.
- Warranty: 1-year limited.
- NEW faster installation, pre-set for GFCI, no insert required.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General

Model Number	WP6000BL
Description	Low-Profile Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hz, Black
UPC Code	078275159167
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications

Number of Included Inserts	2
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle

Dimensions

Lockable Hasp Maximum Diameter (in)	0.19
Lockable Hasp Maximum Diameter (mm)	4.8
Product Dimensions (H x W x D) in	5.5 x 3.75 x 1.5 in
Expandable Depth Mm	54
Expandable Depth In	2 1/8
Accepted Cord Size Max	1x16 AWG
Box Type	Single

Material Specifications

Color	Clear; Black
-------	--------------

Weatherproof Cover Material	UV Stabilized Plastic
-----------------------------	-----------------------

Packaging

Shipping Weight (lbs)	0.35
Product Weight (kg)	0.159
Unit Carton Dimensions (H x W x L) in	1.5 x 3.7 x 5.5 in
Product Weight (lbs)	0.35

Standards and Certifications

UL Certification	cULus
California Proposition 65	None
RoHS Certification	Y