

Weatherproof Cover - Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 3.625" Clear

Item WP1110C



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include adhered gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations
- UL Certified for Type 3R outdoor enclosures
- Meets requirements for cold impact testing: -60° F (-51° C)
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts
- 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws
- Lockable hasp: All models accept up to 1/4" (6 mm) dia shank, except WP3100C & WP3103C accept up to 1/8" (3 mm) dia shank
- Three inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations)
- Max cord size: (2) #14 AWG or (1) #12 AWG
- Mounts vertically or horizontally
- Warranty: 1-year limited

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1110C
Description	Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 3.625" Clear
UPC Code	078275072824
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle
Dimensions	
Lockable Hasp Maximum Diameter (in)	1/4
Lockable Hasp Maximum Diameter (mm)	6
Product Dimensions (H x W x D) in	5.75 x 4 x 3.625 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single
Material Specifications	
Color	Clear



Weatherproof Cover Material	UV Stabilized Plastic
-----------------------------	-----------------------

Packaging

Shipping Weight (lbs)	0.444
Unit Carton Dimensions (H x W x L) in	4.001 x 4.501 x 6.251 in

Standards and Certifications

UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP17
Single-Gang Inserts (3)