

Plug-In Timer - Plug-in timer, Electromechanical Synchronous clock with Manual Override, 24-Hour, 220-240 VAC, 50 Hz, 15 minute Intervals, 16 A, SPDT, E style plug with enhanced child protection - PT 410SE 180

Item 162700041



PRODUCT DESCRIPTION

The PT 410SE analogue plug-in time switch features a daily program and a very short switching time of just 15 minutes, allowing a range of different switching options. In addition, a manual switch enables quick manual switching on and off without affecting programming.

FEATURES

- ▶ 24-hour timer
- ▶ Captured tripper levers with 2-hour increments
- ▶ Easy set clock face
- ▶ E style plug
- ▶ 16 A/250 Vac switching load

APPLICATIONS

- ▶ Indoor Lighting Control

TECHNICAL DATA

General

Model Number	162700041
Description	Plug-in timer, Electromechanical Synchronous clock with Manual Override, 24-Hour, 220-240 VAC, 50 Hz, 15 minute Intervals, 16 A, SPDT, E style plug with enhanced child protection - PT 410SE 180
Country of Origin (Intermatic)	MEXICO

Control Specifications

Minimum ON/OFF Times	15 min
Operation Mode	24 hour
Backup Protection Time	No
Mechanism Type	Analog/Mechanical

Mechanical Specifications

Number of Plugs	1
Plug Configurations	Plug Type E

Dimensions

Product Dimensions (H x W x D) mm	155 x 74 x 81 mm
Product Dimensions (H x W x D) in	6.1 x 2.91 x 3.19 in

Material Specifications

Color	Gray
Housing type	Surface mounted

Load Ratings

Resistive Load Ratings Ranges	16 A / 250 VAC, 21A / 250 VAC (UL)
Inductive Load Ratings Ranges	8 A. 250 VAC

Electrical Specifications

Input Voltage Range(s)	220-240 VAC
Input Voltage Frequencies	50 Hz

Packaging

Shipping Weight (kg)	0.241
Shipping Weight (lbs)	0.531
Product Weight (kg)	0.28
Product Weight (lbs)	0.616

Environmental Specifications

Temperature (operation)	-10 - 55 °C / 14 - 131 °F
Usage Environments	Indoor

Standards and Certifications

Other Certifications and Compatibilities	CE; REACH
RoHS Certification	Y