

## GR\_Hour Meters - Electromechanical Hour Meter, 330-380 VAC, 50 Hz, DIN mount, Gray - HM SD -35 200

Item 052100061



### PRODUCT DESCRIPTION

The HM SD -35 hour meter with AC intended for DIN rail mounting is available in different voltage variants. The device is equipped with undetachable screw terminals and operates mains synchronized within an ambient temperature of -20 °C ... + 55 °C. The meter can monitor up to 99,999.99 hours of operation. The product complies with the safety guidelines of protection class II and protection type IP20. The HM family is characterized by long-life and maintenance-free technology with robust and reliable design.

### TECHNICAL DATA

#### General

Model Number	052100061
Description	Electromechanical Hour Meter, 330-380 VAC, 50 Hz, DIN mount, Gray - HM SD -35 200
Country of Origin (Intermatic)	MEXICO

#### Dimensions

Product Dimensions (H x W x D) mm	100 x 72 x 51 mm
-----------------------------------	------------------

#### Material Specifications

Color	Gray
-------	------

#### Electrical Specifications

Input Voltage Range(s)	230 VAC; 130 VDC
------------------------	------------------

#### Packaging

Shipping Weight (kg)	0.087
Shipping Weight (lbs)	0.191
Product Weight (kg)	0.09
Product Weight (lbs)	0.198
Unit Carton Dimensions (H x W x D) in	1.25 x 0.788 x 2.206 in

#### Environmental Specifications

Temperature (operation)	-20 - 55 °C / - °F
-------------------------	--------------------

#### Standards and Certifications

Other Certifications and Compatibilities	CE; REACH
Compliance	EN 60335-1; EN 60335-2-26
Protection type	IP20

RoHS Certification

Y