

GR_Analog Time Switches - TCC 111.0 STUZH 180 1D SYNC 24HR

Item 017800241



FEATURES

- ▶ 16 A, 250 VAC SPDT switch
- ▶ Synchronous drive
- ▶ Captive tripper levers with 15 minute intervals
- ▶ Manual override, ON-AUTO-OFF
- ▶ Easy-set, true clock face
- ▶ Surface, DIN rail or flush mounting
- ▶ Clear plastic dust cover
- ▶ Compact size

APPLICATIONS

- ▶ Air Movement & Ventilation
- ▶ Distribution/Control Panel
- ▶ Distribution Panel
- ▶ Indoor Lighting Control
- ▶ Landscape Lighting
- ▶ Landscape Water Control
- ▶ Machinery & Pump Controls
- ▶ Motor Control
- ▶ Outdoor Lighting Control
- ▶ Outdoor Water Fountains
- ▶ Pool Pump
- ▶ Pump Control
- ▶ Septic Treatment
- ▶ Timing/Scheduling ON/OFF

TECHNICAL DATA

General

| | |
|--------------------------------|----------------------------------|
| Model Number | 017800241 |
| Description | TCC 111.0 STUZH 180 1D SYNC 24HR |
| UPC Code | 99999999993 |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |
| TARIC HS Code | 9107.00.00 |

Control Specifications

| | |
|------------------|-------------------|
| Clock Drive Type | Synchronous |
| Mechanism Type | Analog/Mechanical |

Dimensions

| | |
|-----------------------------------|------------------------|
| Product Dimensions (H x W x D) mm | 80 x 72 x 55 mm |
| Product Dimensions (H x W x D) in | 3.14 x 2.83 x 2.165 in |

Material Specifications

| | |
|-------|------|
| Color | Gray |
|-------|------|

Load Ratings

| | |
|-----------|---------------------|
| Resistive | 16 A, 250 VAC, 21 A |
| Inductive | 8 A, 250 VAC |

Electrical Specifications

| | |
|---------------------------|----------------------------|
| Input Voltage Range(s) | 220-240 VAC |
| Accuracy | Mains synchronized |
| Current Output | Changeover, Potential-free |
| Load incandescent bulb | 1300 W |
| Input Voltage Frequencies | 50 Hz |

Display and Format

| | |
|-------------------------|-------------------|
| Shortest switching time | ON/OFF 15 minutes |
|-------------------------|-------------------|

Packaging

| | |
|---------------------------------------|------------------------|
| Shipping Weight (kg) | 0.07 |
| Shipping Weight (lbs) | 0.155 |
| Product Weight (kg) | 0.18 |
| Product Weight (lbs) | 0.396 |
| Unit Carton Dimensions (H x W x D) in | 2.175 x 2.851 x 4.2 in |

Operating Specifications

| | |
|---------------|----------------------------|
| Channels | 1 |
| Manual switch | Automatic Mode; Fix ON/OFF |
| Program | Daily Program (ON/OFF) |

Environmental Specifications

| | |
|-------------------------|---------------------------|
| Temperature (operation) | -20 - 55 °C / -4 - 131 °F |
|-------------------------|---------------------------|

Standards and Certifications

| | |
|---------------------------|------|
| Approval mark | CE |
| California Proposition 65 | None |
| RoHS Certification | N/A |