

Plug-In Timer - Plug Module, G style plug with enhanced child protection, 13 A - PM GC

Item 162500022



PRODUCT DESCRIPTION

Type G Modular plug with enhanced contact protection for use with the PT series of plug timers.

FEATURES

- ▶ G style plug
- ▶ Modular plug design

TECHNICAL DATA

| General                           |                                                                        |
|-----------------------------------|------------------------------------------------------------------------|
| Model Number                      | 162500022                                                              |
| Description                       | Plug Module, G style plug with enhanced child protection, 13 A - PM GC |
| UPC Code                          | 999999999993                                                           |
| Country of Origin (Intermatic)    | MEXICO                                                                 |
| Warranty Period                   | 1-Year limited                                                         |
| TARIC HS Code                     | 8536.69.90.99                                                          |
| Mechanical Specifications         |                                                                        |
| Number of Plugs                   | 1                                                                      |
| Plug Configurations               | Plug Type G                                                            |
| Dimensions                        |                                                                        |
| Product Dimensions (H x W x D) mm | 48 x 41 x mm                                                           |
| Product Dimensions (H x W x D) in | 1.89 x 1.61 x in                                                       |
| Material Specifications           |                                                                        |
| Color                             | Light Gray                                                             |
| Housing Material                  | Thermoplastics, self-extinguishing & high-temperature resistant        |
| Load Ratings                      |                                                                        |
| Resistive Load Ratings Ranges     | 13 A, 250 VAC                                                          |
| Electrical Specifications         |                                                                        |
| Input Voltage Range(s)            | 230 VAC                                                                |
| Input Voltage Frequencies         | 50 or 60 Hz                                                            |
| Packaging                         |                                                                        |
| Shipping Weight (kg)              | 0.094                                                                  |
| Shipping Weight (lbs)             | 0.208                                                                  |



|                                       |                       |
|---------------------------------------|-----------------------|
| Product Weight (kg)                   | 0.08                  |
| Product Weight (lbs)                  | 0.176                 |
| Unit Carton Dimensions (H x W x D) in | 2.104 x 1.73 x 2.8 in |
| Units Per Pallet                      | 4608                  |

Environmental Specifications

|                         |                           |
|-------------------------|---------------------------|
| Temperature (operation) | -10 - 55 °C / 14 - 131 °F |
| Usage Environments      | Indoor                    |

Standards and Certifications

|                                          |                                                                   |
|------------------------------------------|-------------------------------------------------------------------|
| Other Certifications and Compatibilities | TUV                                                               |
| Standards and Guidelines                 | EN 60730-1, Mode of operation and additional properties: Type 1.B |
| California Proposition 65                | None                                                              |
| RoHS Certification                       | Y                                                                 |