

In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 4 Hour Max, Without Hold, Ivory, Mexico Sales Only

Item FD4HMX



PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads.

*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- 4-Hour
- SPST (Single-Pole Single-Throw)
- Breaks circuit at end of timing cycle
- No electricity required to operate
- Replaces any standard or decorator single- or multi-gang wall switch
- Automatically limits ON time for energy consuming loads
- Quick and easy installation
- Time-saving up front terminal connection with teeter-type terminals
- Incandescent/fluorescent/CFL/LED compatible
- No neutral connection is required

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Motor Control
- Air Movement & Ventilation

TECHNICAL DATA

General

| | |
|--------------------------------|--|
| Model Number | FD4HMX |
| Description | Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 4 Hour Max, Without Hold, Ivory, Mexico Sales Only |
| UPC Code | 078275074019 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | TUNISIA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|-----------------------------|-------------------------------------|
| Operation Mode | Countdown |
| Countdown Time | 4 hrs |
| Hold Mode Included | No |
| Mechanism Type | Analog/Mechanical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |

Mechanical Specifications

| | |
|---------------------------|-------------------------|
| Wall Plate Configurations | Single-Gang; Multi-Gang |
|---------------------------|-------------------------|

Dimensions

| | |
|-----------------------------------|------------------------|
| Product Dimensions (H x W x D) in | 4.125 x 1.75 x 1.25 in |
|-----------------------------------|------------------------|

Material Specifications

| | |
|-------|-------|
| Color | Ivory |
|-------|-------|

Load Ratings

| | |
|----------------------------------|---|
| Resistive Heater | 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC |
| Tungsten (Incandescent) Range(s) | 7 A, 125 VAC, 50/60 Hz, 875 W |
| Motor Load Ratings Ranges | 1 HP, 125 VAC; 2 HP, 250 VAC |

Electrical Specifications

| | |
|-----------------------------|-----------------------|
| Input Voltage Range(s) | 125-277 VAC, 50/60 Hz |
| Wiring Configurations | Single |
| Switch Type | SPST |
| Neutral Connection Required | No |
| Hz | 50/60 |

Environmental Specifications

| | |
|-------------------------|-------------------------|
| Temperature (operation) | 32 - 104 °F / 0 - 40 °C |
|-------------------------|-------------------------|

Packaging

| | |
|---------------------------------------|-----------------------|
| Shipping Weight (lbs) | 0.301 |
| Unit Carton Dimensions (H x W x D) in | 4.63 x 2.13 x 2.88 in |

Standards and Certifications

| | |
|--|--------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | NOM |
| California Proposition 65 | None |
| RoHS Certification | N/A |

ACCESSORIES



148FD5076

Plate for 4-Hr without HOLD, Ivory
(FD34H, FD4H)



146--00045

Knob-Wall Switch FD Series - Ivory



146--00046

Knob-Wall Switch FD Series - White



146--00047

Knob-Wall Switch FD Series - Almond



146MT416A

Knob-Wall Switch FD Series - Black