

In-Wall Timer - Heavy-Duty 7-Day Programmable Timer

Item ST01K



PRODUCT DESCRIPTION

Highly versatile heavy-duty timers are ideal for any application that requires a simple or complex ON/OFF schedule, regardless of load. No neutral connection is required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ Versatile 7-day programmable schedules with up to 40 ON/OFF events.
- ▶ Astronomic clock feature determines dawn and dusk times.
- ▶ Automatic daylight saving time (DST) adjustment.
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance.
- ▶ Single or 3-way switch compatible. No neutral wire connection enables easy retrofitting and quicker installation.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ Isolated switch allows timer to be used with any load type, including AC and DC loads.
- ▶ Replaceable CR2 lithium battery provides up to three years of operation.
- ▶ Decorator switch plate not included.
- ▶ Programmable Countdown feature

TECHNICAL DATA

General	
Model Number	ST01K
Description	Heavy-Duty 7-Day Programmable Timer
UPC Code	078275145467
Brand	Intermatic
Country of Origin (Intermatic)	VIETNAM
Warranty Period	1-Year limited
Control Specifications	
Maximum ON/OFF Operations	40
Operation Mode	24 hour; Countdown
Operation Features	Astronomic; Countdown; Daylight Saving Time
Countdown Time	24 hrs
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	3 Years
Battery Type	CR2
Battery Service Type	Replaceable
Minimum ON/OFF Times	1 min
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Lithium Manganese Dioxide (LiMnO ₂)
Battery Weight (grams)	11
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	1
Watt Hours Per Battery	3.0
Lithium Content (grams) in Battery	0.5
Mechanical Specifications	

Wall Plate Configurations

Single-Gang

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.813 in

Material Specifications

Color White

Finish Gloss

Load Ratings

Resistive Heater 15 A, 120-277 VAC

Tungsten (Incandescent) Range(s) 1800 W, 120 VAC; 1248-1662 W, 208-277 VAC

Ballast Fluorescent 8 A, 120 VAC; 4 A, 208-277 VAC

Electronic Ballast LED 5 A, 120 VAC; 2 A, 277 VAC

DC Loads 4 A, 12 VDC; 2 A, 28 VDC

Motor Load Ratings Ranges 1 HP, 120 VAC; 2 HP, 240 VAC

Max Load Handling Capability 15 A

Inductive Load Ratings Ranges 8 A, 120 VAC, 50/60 Hz; 4 A, 208-277 VAC, 50/60 Hz

Electrical Specifications

Input Voltage Range(s) 120-277 VAC, 50/60 Hz

Wiring Configurations Single; 3-Way

Neutral Connection Required No

Hz 50/60

Amperage 15 A

Environmental Specifications

Temperature (operation) 32 - 104 °F / 0 - 40 °C

Packaging

Shipping Weight (lbs) 0.4

Unit Carton Dimensions (H x W x D) in 4.625 x 2.125 x 2.875 in

Standards and Certifications

UL Certification cULus

Other Certifications and Compatibilities Title 20; Green Energy

California Proposition 65 DEHP

RoHS Certification N/A