

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Ivory

Item EI210



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from 10 minutes to 1 hour
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

| General                           |                                                                                               |
|-----------------------------------|-----------------------------------------------------------------------------------------------|
| Model Number                      | EI210                                                                                         |
| Description                       | Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Ivory |
| UPC Code                          | 078275095229                                                                                  |
| Brand                             | Intermatic                                                                                    |
| Country of Origin (Intermatic)    | CHINA                                                                                         |
| Warranty Period                   | 1-Year limited                                                                                |
| Control Specifications            |                                                                                               |
| Time Presets                      | 10 min; 20 min; 30 min; 60 min                                                                |
| Setpoint Program Count            | 4                                                                                             |
| Operation Mode                    | Countdown                                                                                     |
| Countdown Time                    | 60 min                                                                                        |
| Hold Mode Included                | Yes                                                                                           |
| Mechanism Type                    | Digital/Electrical                                                                            |
| Application Compatibilities       | Incandescent; Fluorescent; CFL; LED                                                           |
| Mechanical Specifications         |                                                                                               |
| Wall Plate Configurations         | Single-Gang                                                                                   |
| Dimensions                        |                                                                                               |
| Product Dimensions (H x W x D) in | 4.125 x 1.688 x 1.438 in                                                                      |
| Material Specifications           |                                                                                               |



|        |       |
|--------|-------|
| Color  | Ivory |
| Finish | Gloss |

Load Ratings

|                                  |              |
|----------------------------------|--------------|
| Resistive Heater                 | 15 A, 1800 W |
| Tungsten (Incandescent) Range(s) | 1000 W       |
| Ballast Fluorescent              | 8 A, 1000 VA |
| Electronic Ballast LED           | 4 A, 500 VA  |
| Motor Load Ratings Ranges        | 1/4 HP       |

Electrical Specifications

|                             |                |
|-----------------------------|----------------|
| Input Voltage Range(s)      | 120 VAC, 60 Hz |
| Wiring Configurations       | Single         |
| Neutral Connection Required | Yes            |
| Hz                          | 60             |

Environmental Specifications

|                         |                         |
|-------------------------|-------------------------|
| Temperature (operation) | 32 - 104 °F / 0 - 40 °C |
|-------------------------|-------------------------|

Packaging

|                                       |                    |
|---------------------------------------|--------------------|
| Shipping Weight (lbs)                 | 0.349              |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 3 x 2.13 in |

Standards and Certifications

|                                          |              |
|------------------------------------------|--------------|
| UL Certification                         | cULus        |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | DEHP         |
| RoHS Certification                       | Y            |