

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Light Almond

Item EI210LA



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required
- Provides silent operation in time ranges from 10 minutes to 1 hour
- Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- Replaces single-pole switches in a variety of applications
- Incandescent/fluorescent/CFL/LED compatible
- For use with decorator-style wall plate (not included)
- Requires neutral connection

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	EI210LA
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 10,20,30,60 Minute, With Hold, Light Almond
UPC Code	078275100589
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Time Presets	10 min; 20 min; 30 min; 60 min
Setpoint Program Count	4
Operation Mode	Countdown
Countdown Time	60 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
-----------------------------------	--------------------------

Material Specifications

Color Light Almond

Load Ratings

Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST-NO
Neutral Connection Required	Yes
Hz	60

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.399
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y