

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Light Almond

Item EI235LA



 UL

PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required
- Provides silent operation in time ranges from 15 minutes to 2 hours
- Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- Replaces single-pole switches in a variety of applications
- Incandescent/fluorescent/CFL/LED compatible
- For use with decorator-style wall plate (not included)
- Requires neutral connection

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | EI235LA |
| Description | Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Light Almond |
| UPC Code | 078275111196 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|-----------------------------|-------------------------------------|
| Time Presets | 15 min; 30 min; 45 min; 1 hr; 2 hrs |
| Setpoint Program Count | 5 |
| Operation Mode | Countdown |
| Countdown Time | 2 hrs |
| Hold Mode Included | No |
| Mechanism Type | Digital/Electrical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |

Mechanical Specifications

| | |
|---------------------------|-------------|
| Wall Plate Configurations | Single-Gang |
|---------------------------|-------------|

Dimensions

| | |
|-----------------------------------|--------------------------|
| Product Dimensions (H x W x D) in | 4.125 x 1.688 x 1.438 in |
|-----------------------------------|--------------------------|

Material Specifications

Color Light Almond

Load Ratings

| | |
|----------------------------------|--------------|
| Resistive Heater | 15 A, 1800 W |
| Tungsten (Incandescent) Range(s) | 1000 W |
| Ballast Fluorescent | 8 A, 1000 VA |
| Electronic Ballast LED | 4 A, 500 VA |
| Motor Load Ratings Ranges | 1/4 HP |

Electrical Specifications

| | |
|-----------------------------|----------------|
| Input Voltage Range(s) | 120 VAC, 60 Hz |
| Wiring Configurations | Single |
| Neutral Connection Required | Yes |
| Hz | 60 |

Environmental Specifications

| | |
|-------------------------|-------------------------|
| Temperature (operation) | 32 - 104 °F / 0 - 40 °C |
|-------------------------|-------------------------|

Packaging

| | |
|---------------------------------------|--------------------|
| Shipping Weight (lbs) | 0.4 |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 3 x 2.13 in |

Standards and Certifications

| | |
|---------------------------|-------|
| UL Certification | cULus |
| California Proposition 65 | None |