

## In-Wall Timer - Spring Wound Countdown Timer - Commercial

Item SW60MK



### PRODUCT DESCRIPTION

The SW Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads.

\*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- 60-Minute timer
- SPST (Single-Pole Single-Throw)
- Breaks circuit at end of timing cycle
- No electricity required to operate
- Replaces any standard or decorator single-gang wall switch
- Automatically limits ON time for energy consuming loads
- Quick and easy installation
- Time-saving up front terminal connection with teeter-type terminals
- Brushed metal look switch plate meets NEC requirements (plate is included)
- Incandescent/fluorescent/CFL/LED compatible

### TECHNICAL DATA

#### General

Model Number	SW60MK
Description	Spring Wound Countdown Timer - Commercial
UPC Code	078275143531
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited

#### Control Specifications

Operation Mode	Countdown
Countdown Time	60 min
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang; Multi-Gang
---------------------------	-------------------------

#### Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.25 in
-----------------------------------	------------------------

#### Material Specifications

Color	Silver
Includes Wall Plate	Yes
Finish	Matte

#### Load Ratings

Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten (Incandescent) Range(s)	7 A, 125 VAC, 50/60 Hz, 875 W

Motor Load Ratings Ranges 1 HP, 125 VAC; 2 HP, 250 VAC

#### Electrical Specifications

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	SPST
Watts	2500
Hz	50/60
Amperage	8 A

#### Environmental Specifications

Temperature (operation)	40 - 120 °F / 4 - 49 °C
-------------------------	-------------------------

#### Packaging

Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	4.625 x 2.125 x 2.875 in

#### Standards and Certifications

UL Certification	RU
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP