

## In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Removable Trippers, White

Item E1020



### PRODUCT DESCRIPTION

These Heavy-Duty In-Wall Timers are ideal for turning on lights, fans, pumps and other heavy duty loads for energy savings, security and convenience. The timer provides up to 12 ON and 12 OFF operations per day.

### FEATURES

- E1010 includes one ON/OFF permanently attached tripper for single ON/OFF control per 24-hour period
- E1020 includes two ON/OFF trippers and can accommodate up to 12 ON/OFF trippers
- Programmable in 30-minute intervals
- Turns ON/OFF heavy-duty loads for energy savings, security and convenience
- Mounts to any standard junction box
- Requires neutral connection

### APPLICATIONS

- Air Movement & Ventilation
- Indoor Lighting Control
- Outdoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	E1020
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Removable Trippers, White
UPC Code	078275440203
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Maximum ON/OFF Operations	12
Operation Mode	24 hour
Mechanism Type	Analog/Mechanical
Minimum ON/OFF Times	30 min
Application Compatibilities	Incandescent; Fluorescent; CFL

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

#### Dimensions

Product Dimensions (H x W x D) in	4.25 x 3.25 x 1.375 in
-----------------------------------	------------------------

#### Material Specifications

Color	White
Includes Wall Plate	Yes
Finish	Gloss

**Load Ratings**

Motor Load Ratings Ranges	12 FLA @ 125 VAC, 60 Hz
Incandescent Load Ratings (Single-Gang)	1500 W, 125 VAC, 60 Hz
Incandescent Single Gang Load Ratings Ranges	1500 W, 125 VAC, 60 Hz
Resistive Load Ratings Ranges	15 A, 125 VAC, 60 Hz

**Electrical Specifications**

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Supply Voltage	125 volt
Watts	1500
Hz	60
Amperage	15 A

**Environmental Specifications**

Temperature (operation)	-4 - 77 °F / -20 - 25 °C
-------------------------	--------------------------

**Packaging**

Shipping Weight (lbs)	0.748
Unit Carton Dimensions (H x W x D) in	3.251 x 3.501 x 5.751 in

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Nickel
RoHS Certification	N/A

---

**ACCESSORIES**



156EB1945A  
Trippers for E1020 (Pack of 2)



48EB937  
Spring - Cam Passivate for E1020 and WH21



48EB938  
Spring - Cam Green for E1020 and WH21



WG230-13  
Motor - 125 V 60 Hz with Leads & Cover