

## In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30 Minute,1,2,4 Hour, Without Hold, White

Item EI215W



### PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- ▶ No programming required.
- ▶ Provides silent operation in time ranges from 15 minutes to 4 hours.
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation.
- ▶ Replaces single-pole switches in a variety of applications.
- ▶ Incandescent/fluorescent/CFL/LED compatible.
- ▶ For use with decorator-style wall plate (not included).
- ▶ Requires neutral connection.

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

#### General

Model Number	EI215W
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30 Minute,1,2,4 Hour, Without Hold, White
UPC Code	078275108509
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

#### Control Specifications

Time Presets	15 min; 30 min; 1 hr; 2 hrs; 4 hrs
Setpoint Program Count	5
Operation Mode	Countdown
Countdown Time	4 hrs
Hold Mode Included	No
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

#### Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
-----------------------------------	--------------------------

#### Material Specifications

Color

White

**Load Ratings**

Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP

**Electrical Specifications**

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Hz	60

**Environmental Specifications**

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

**Packaging**

Shipping Weight (lbs)	0.349
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y