

## In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer Only, 120 VAC, 20A, 1 Gang, SPST, White

Item KM2ST-1G



  

### PRODUCT DESCRIPTION

For installing on circuits up to 20 A, this timer provides automatic 24-hour ON/OFF control of outdoor/indoor lighting, fans, pumps, office equipment and other types of loads.

### FEATURES

- 72 trippers provide 36 ON/OFF events per 24-hour period
- Captive trippers with 20-minute switching intervals
- 3-way (SPDT) switch available
- 3-position ON/OFF/AUTO override provides continuous ON or OFF operation
- Reliable synchronous timer motor
- Multiple wall plates available
- Easy wiring and installation
- Heavy-Duty 20 A rating
- Requires neutral connection

### APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation
- Outdoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	KM2ST-1G
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, Timer Only, 120 VAC, 20A, 1 Gang, SPST, White
UPC Code	078275153660
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Maximum ON/OFF Operations	36
Operation Mode	24 hour
Hold Mode Included	No
Mechanism Type	Analog/Mechanical
Minimum ON/OFF Times	20 min
Application Compatibilities	Incandescent; Fluorescent; CFL

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

#### Material Specifications

Color	White
Includes Wall Plate	No
Finish	Matte

<b>Communication Method</b>	
Has WiFi	No
Has Bluetooth	No
<b>Load Ratings</b>	
Motor Load Ratings Ranges	1 HP, 120 VAC, 60 Hz
Incandescent Load Ratings (Single-Gang)	1350 W, 120 VAC, 60 Hz
Incandescent Single Gang Load Ratings Ranges	1350 W, 120 VAC, 60 Hz
Inductive Load Ratings Ranges	8 A, 120 VAC, 60 Hz
<b>Electrical Specifications</b>	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Switch Type	SPST
Neutral Connection Required	Yes
Wiring Option	SPST (3) #14 AWG color coded; SPDT (4) #14 AWG color coded
Hz	60
Amperage	20 A
<b>Environmental Specifications</b>	
Operating Humidity	0 to 95%, Non-condensing
Usage Environments	Indoor; Outdoor
Temperature (operation)	-40 - 180 °F / -40 - 82 °C
<b>Packaging</b>	
Shipping Weight (lbs)	0.379
Unit Carton Dimensions (H x W x D) in	3 x 3 x 4 in
<b>Standards and Certifications</b>	
UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

---

## ACCESSORIES



24--00109

Wall Plate for KM2ST-1G or KM2STU-1G, Single Gang, White