

Electronic Timer Control - 24-Hour/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure

Item ET2115C



  

PRODUCT DESCRIPTION

The ET2000 Series offers an easy-to-use interface, while still allowing to-the-minute scheduling capabilities for nearly any application. This series provides 50 holiday blocks with independent scheduling to ensure the loads are always in the proper ON/OFF state. This series also includes 96 ON/OFF events for even the most demanding schedules. The scheduling capabilities, configurable outputs, and a 100-hour backup without the need of batteries, make this series ideal for nearly any application. They come in standard 24-hour versions.

FEATURES

- 100-hour supercapacitor eliminates the need for batteries.
- Up to 96 set points or events.
- Up to 50 holiday blocks with schedule capabilities.
- Automatic input voltage selection from 120 to 277 VAC, 60 Hz.
- Additional mode of operation turns the ON/OFF buttons into 2-hour overrides.
- Configurable outputs allow the control of various voltages and applications.
- Relays incorporate zero-crossing technology to extend the life of the control.
- Non-volatile EEPROM memory protects programming indefinitely.
- LED compatible.
- USB port makes transferring and saving of schedules easy.

APPLICATIONS

- Indoor Lighting Control
- Timing/Scheduling ON/OFF
- Machinery & Pump Controls

TECHNICAL DATA

General

Model Number	ET2115C
Description	24-Hour/365 Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure
UPC Code	078275147980
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	2-Year limited

Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Maximum ON/OFF Operations	96
Setpoint Program Count	96
ON/OFF Operations	96
Operation Features	Holiday
Operation Mode	24 hour
Daylight Savings Adjustment	Automatic
Backup Restoration Time	30 Minutes
Backup Type	Supercapacitor
Backup Protection Time	100 Hour
Application Compatibilities	LED

Mechanical Specifications

Enclosure Type	Indoor type 1 metal
----------------	---------------------

Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Material Specifications

Color	Gray
-------	------

Communication Method

Has WiFi	No
----------	----

Load Ratings

Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Magnetic Ballast (NC) Range(s)	3 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 20 A, 120-240 VAC
Resistive (NC) Range(s)	10 A, 28 VDC; 10 A, 120-240 VAC
Inductive Load Ratings NC Ranges	10 A, 120-240 VAC
Inductive Load Ratings NO Ranges	30 A, 120-240 VAC
Electronic Ballast Load Ratings NO Ranges	10 A, 120/277 VAC
Motor Load Ratings NC Ranges	1/4 HP, 120 VAC; 1/2 HP, 240 VAC
Motor Load Ratings NO Ranges	1 HP, 120 VAC; 2 HP, 240 VAC

Electrical Specifications

Voltage Selection Type	Auto-Voltage
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPDT
Maximum Power Consumption (W)	3 W
Electronic Series	ET2000 Series
Hz	60

Packaging

Shipping Weight (lbs)	2.85
Unit Carton Dimensions (H x W x L) in	8 x 3.15 x 5.236 in

Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
------------------	-------

Other Certifications and Compatibilities	LED; Title 20; Green Energy +
California Proposition 65	Lead
RoHS Certification	N/A